


Eaton C25FNF375C

Catalog Number: C25FNF375C

Eaton definite purpose contactor, Quick, 300A, 110-120 Vac, 50/60 Hz, 1NO, 1NC, Open with metal mounting plate, 15-50A, two- and three-pole, 300A, Contactor, Three-pole, 300A, Box lugs (posidrive setscrew), Non-reversing



General specifications

Product Name	Catalog Number
Eaton definite purpose contactor	C25FNF375C
UPC	Product Length/Depth
782114623640	3.97 in
Product Height	Product Width
3.75 in	2.63 in
Product Weight	Warranty
1 lb	1 year
Compliances	Certifications
RoHS Compliant	UL Recognized CSA Certified

defaultTaxonomyAttributeLabel

Amperage Rating

60A

Number Of Poles

Three-pole

Type

Definite Purpose Control Contactor

Auxiliary contacts

1 NO, 1 NC

Coil

110-120 Vac, 50/60 Hz

Enclosure

Open with metal mounting plate

Frame size

15-50 A, two-pole and three-pole

Inductive full load

75 A

Model

Contactors

Resistive load

90 A

Terminals

Box lugs (posidrive setscrew) and quick connect terminals (side-by-side)

Connection

Quick

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Drawings

[C25FNF3 AutoCAD 2D Footprint \(mm\)](#)

[C25FNF3 3D Inventor](#)

[C25FNF3 3D Model Xchange](#)

[C25FNF3 AutoCAD 2D Footprint](#)

[C25FNF3 2D PDF](#)

Specifications and datasheets

[Eaton Specification Sheet - C25FNF375C](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)