Eaton DM1-344D3NB-S20S

Catalog Number: DM1-344D3NB-S20S

Eaton PowerXL DM1 series micro drive, Three-phase, 400 V, 4.3 A, Internal brake chopper, Multi segment LCD display, IP20, ST0 SIL2 and ethernet I/P, Modbus TCP onboard

General specifications

Product Name

Eaton PowerXL DM1 micro variable

frequency drive

7

Product Length/Depth

11.4 in

Product Width

5.4 in

Certifications

UL Listed

Catalog Number

DM1-344D3NB-S20S

UPC

786689349462

Product Height

9.7 in

Product Weight

3.45 lb



default Taxonomy Attribute LabelBrake chopper Internal brake chopper Series DM1 Drive type General purpose Frame size FR1 **Enclosure rating** IP00 Input phases Three-phase Output phases Three-phase Electromagnetic compatibility filter No Internal choke No Internal line reactor

Ambient operating temperature range

-10 to 50 °C CT -10 to 40 °C VT

Conformal coated boards

No

Yes

User interface Multi-segment

Input voltage range 380-480 Vac

Input frequency range

Output frequency range

50-60 Hz

0-400 Hz

200 %

Max overload

Specifications and datasheets

Resources

Eaton Specification Sheet - DM1-344D3NB-S20S

| Mounting Type |
|---|
| Panel mount DIN rail |
| Digital inputs 4 |
| Analog inputs 1 |
| Relay outputs 2 |
| Digital outputs 0 |
| High overload (CT) hp |
| High overload (CT) kW 1.5 |
| Low overload (VT) kW 2.2 |
| Low overload (VT) amps 5.6 |
| High overload (CT) amps 4.3 |
| Low overload (VT) hp 3 |
| Communications onboard Modbus RTU Modbus TCP Ethernet/IP BACnet IP BACnet MS/TP Bluetooth |
| Communications optional CANopen PROFIBUS SmartWireDT |
| Motor control modes V/Hz |

Open loop vector control

Fuse size - max

15

Motor type

Induction

Induction motor

Permanent magnet motor (SPM/IPM)



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia