

Eaton E65-SMPR3-GL

Catalog Number: E65-SMPR3-GL

Eaton SM Series Rectangular Body Photoelectric Sensor, Sensor dist 10 Ft, 200 mA max AC/DC, AC: L1 Switched, DC: NPN Open Collector, 200 mA DC NPN/AC 3-Wire, 6.6 Ft. (2m) Cable, 18–264 Vac/18–50 Vdc input, 6.6 Ft. (2m)



General specifications

Product Name	Catalog Number
Eaton E65 SM compact photoelectric sensor	E65-SMPR3-GL
	UPC
	782114389911
Product Length/Depth	Product Height
2.17 in	1.29 in
Product Width	Product Weight
1.63 in	0.1938 lb
Warranty	Compliances
3 year	CE Marked
Certifications	Catalog Notes
UL Listed cUL Listed	For complete system; order sensor and retroreflector. Retroreflector not included

defaultTaxonomyAttributeLabel

Contact Rating

200 mA DC NPN / 200 mA AC 3 - Wire

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Cable jacket: PVC

Lens: polycarbonate

Body: cycloloy

Operating mode

Polarized retroreflective

Connection

6.6 ft (2 m) cable

Contact configuration

AC: L1 switched

DC: NPN open collector

Sensor type

Polarized retroreflective

Switch type

Photoelectric

Input voltage

18-264 Vac, 18-50 Vdc

LED indicator

Power on: green

Marginal gain: orange

Output status: red

Cord length

79.2 ft

Maximum AC current

200 mA

Maximum DC current

200 mA

Operating temperature - max

131 °F

Operating temperature - min

-13 °F

Resources

Brochures

[Test the Best Photoelectric Sensors: SM Series](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

[Product Range Catalog Sensors – products, basic information, applications](#)

Specifications and datasheets

[Eaton Specification Sheet - E65-SMPR3-GL](#)

Environmental rating

NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P,
NEMA 12, NEMA 13, IP68, IP69K



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)