

Eaton E65-SMTD15-HL

Catalog Number: E65-SMTD15-HL

Eaton Photoelectric Sensor, E65, Through Beam, Forward Viewing, Power (green), output (red), TargetLock (orange), 6.6 ft, 100 mA at 10-30 Vdc, PVC, NPN and PNP open collector, 10-30 Vdc



General specifications

Product Name	Catalog Number
Eaton E65 SM compact photoelectric sensor	E65-SMTD15-HL
	UPC
	782114390030
Product Length/Depth	Product Height
1.29 in	1.47 in
Product Width	Product Weight
2.17 in	0.25 lb
Warranty	Compliances
3 year	CE Marked
Certifications	
cUL Listed	
UL Listed	

defaultTaxonomyAttributeLabel

Type

Photoelectric Sensor

Contact Rating

100 mA at 10-30 Vdc

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Cable jacket: PVC

Lens: polycarbonate

Body: cycology

Contact configuration

NPN and PNP open collector

Series

E65

Sensor type

Through beam

Input voltage

10-30 Vdc

LED indicator

TargetLock: orange

Power: green

Output: red

Protection

Auto reset short circuit

Cord length

79.2 ft

Maximum DC current

100 mA

Operating temperature - max

131 °F

Operating temperature - min

-13 °F

Environmental rating

NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P,
NEMA 12, NEMA 13, IP68, IP69K 2

Resources

Brochures

[Test the Best Photoelectric Sensors: SM Series](#)

Catalogs

[Product Range Catalog Sensors – products, basic information, applications](#)

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - E65-SMTD15-HL](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)