

Eaton E65-SM-TS15-HAD

Catalog Number: E65-SM-TS15-HAD

Eaton SM Series Rectangular Body Photoelectric Sensor, Photoelectric, Right Angle, Sensor distance: 49 Ft., Lens: polycarbonate cable jacket: PVC body: Cyloloy enclosure, 4 Pin M12 Connector, 10-30 Vdc input, Thru-beam

General specifications



Product Name	Catalog Number
Eaton E65 SM compact photoelectric sensor	E65-SM-TS15-HAD
	UPC
	782114786543
Product Length/Depth	Product Height
2.17 in	1.29 in
Product Width	Product Weight
1.47 in	0.0688 lb
Warranty	Compliances
3 year	CE Marked
Certifications	Catalog Notes
cUL Listed UL Listed	For complete system; order 1 source and 1 detector

defaultTaxonomyAttributeLabel

Type

Photoelectric Sensor; SM Series

Cable type

Polyvinyl Chloride (PVC)

Enclosure material

Lens: polycarbonate

Body: cycloloy

Cable jacket: PVC

Operating mode

Thru-beam

Connection

4-pin M12 connector

Sensor type

Through beam

Switch type

Photoelectric

Input voltage

10-30 Vdc

LED indicator

Power on: green

Operating temperature - max

131 °F

Operating temperature - min

-13 °F

Environmental rating

NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P,
NEMA 12, NEMA 13, IP68, IP69K

Resources

Brochures

[Test the Best Photoelectric Sensors: SM Series](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

[Product Range Catalog Sensors – products, basic information, applications](#)

Specifications and datasheets

[Eaton Specification Sheet - E65-SMTS15-HAD](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)