

# Eaton E59-A30A112C02-CV

Catalog Number: E59-A30A112C02-CV

Eaton AccuProx Series Tubular Analog Output Inductive Proximity Sensor Enclosure, 1.18 dia, Straight, Sensor dist. 12 mm, Tube: Stainless Steel, 6.6 Ft. (2m) Cable, 15-30 Vdc input, < 50um after 1 hour warmup accuracy, Shielded



## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton E59 AccuProx analog inductive proximity sensor	E59-A30A112C02-CV
	<b>UPC</b>
	786685104683
<b>Product Length/Depth</b>	<b>Product Height</b>
1.18 in	2.74 in
<b>Product Width</b>	<b>Product Weight</b>
1.18 in	0.6063 lb
<b>Warranty</b>	<b>Compliances</b>
1 year	CE Marked
<b>Certifications</b>	
UL Listed	
CSA Certified	

## defaultTaxonomyAttributeLabel

### Actuator function

Shielded

### Cable type

Polyvinyl Chloride (PVC)

### Accuracy

< 50 um after 1 hour warmup

### Enclosure material

End bell: polycarbonate

Front cap: polyphenylene sulfide

Tube: stainless steel

### Connection

6.6 ft (2 m) cable

### Series

E59

### Sensor type

Analog inductive proximity

Inductive proximity

### Environmental rating

NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13,  
IP67, IP69K

### Cord length

79.2 ft

### Operating temperature - max

158 °F

### Operating temperature - min

-40 °F

### Input voltage

15-30 Vdc

### Protection

Reverse polarity and short circuit

## Resources

### Brochures

[AccuProx analog sensor](#)

### Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

### Multimedia

[We make what matters](#)

### Specifications and datasheets

[Eaton Specification Sheet - E59-A30A112C02-CV](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com  
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)