

Date:	Project Name:
Type:	Part Number:



SABRE SERIES

LED LINEAR STRIP

DESCRIPTION

Reno Lighting's Sabre Series is the LED ECO Commercial Strip fixture is designed with a polycarbonate diffuser that provides impact resistance and even, low glare light. Combine this with powerful, high output LED chips, these fixtures meet today's stringent efficacy standards and bring your projects maximum energy savings.

FEATURES

- DLC Premium for the Stairwell and Passageway Luminaires
- 0-10V dimming control compatible
- Surface or Suspension mounting options
- Operating temperature: -22°F to +122°F (-30°C to +50°C)
- Dual Voltage 120-347V
- Easy and Safe Installation
- Frosted Polycarbonate Lens
- Suitable for Damp Location
- CRI >80
- Rated Lifetime L70(hrs): >70,000
- Includes J-Box Coverplate and V-Hangers
- Multi CCT & Wattage
- 5 year warranty

APPLICATIONS

- Parking Garage
- Stairwell / Passageway
- Warehouse



Date:	Project Name:
Type:	Part Number:

SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	CCT (K)	LUMENS	EFFICACY	CRI
R33022	RENO-LSN4-DV-MCCT-MW-ECO	20W	120-347V	3500K	2460 lm	123 lm/W	>80
		30W			3660 lm	122 lm/W	
		40W			4836 lm	120.9 lm/W	
		20W		4000K	2720 lm	136 lm/W	>80
		30W			4050 lm	135 lm/W	
		40W			5360 lm	134 lm/W	
		20W		5000K	2500 lm	125 lm/W	>80
		30W			3720 lm	124 lm/W	
		40W			4920 lm	123 lm/W	
R33023	RENO-LSN8-DV-MCCT-MW-ECO	40W	120-347V	3500K	4920 lm	123 lm/W	>80
		60W			7320 lm	122 lm/W	
		80W			9554 lm	119.4 lm/W	
		40W		4000K	5440 lm	136 lm/W	>80
		60W			8100 lm	135 lm/W	
		80W			10,720 lm	134 lm/W	
		40W		5000K	5000 lm	125 lm/W	>80
		60W			7440 lm	124 lm/W	
		80W			9840 lm	123 lm/W	

DLC CHART

ORDER#	MODEL#	APPLICATION	DLC	
			STANDARD	PREMIUM
R33022	RENO-LSN4-DV-MW-MCCT-ECO	Direct Linear Ambient Luminaires	P08KVTQ4	
		Stairwell and Passageway Luminaires		S-M9R7UG
R33023	RENO-LSN8-DV-MW-MCCT-ECO	Direct Linear Ambient Luminaires	P7SRLY9D	
		Stairwell and Passageway Luminaires		S-QJUBNX

Date:	Project Name:
Type:	Part Number:


ACCESSORIES OPTIONS

ORDER#	MODEL#	DESCRIPTION
R39307	I-BRACKET	I-Bracket for straight continuous Installation
R83004	RENO-EM-C08	Emergency LED Driver

SENSOR OPTIONS


ORDER#	MODEL#	DESCRIPTION
R74002	RENO-SENSOR-PIR-H-EX	For external mounting when installed above 13FT

DIMENSIONS



53.3mm
(2.1")

4FT



1219.2mm (48")



8FT



2438.4mm (96")

