

# REL-FO/LRC-120AC/2X21/MS - Single relay



1308316

<https://www.phoenixcontact.com/in/products/1308316>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Plug-in miniature relay with mechanical switching position indicator, FASTON connection, 2 changeover contacts, status display: Yellow LED, RC element, Input voltage: 120 V AC

## Commercial data

Item number	1308316
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	CK6
Product key	CK6193
GTIN	4063151558925
Weight per piece (including packing)	28.15 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85364900
Country of origin	CN

## Technical data

### Notes

General	Do not use to separate SELV/PELV circuits from other circuits, because safe isolation is not guaranteed. (applies to the optocoupler variants)
General	The outputs are not suitable for switching different outer conductors.
General	The system installer must ensure the touch protection of the product (at voltages > 25 V AC/60 V DC). The product is a built-in device without protection against direct contact.

### Product properties

Product type	Single relay
Product family	ESSENTIAL edition
Operating mode	100% operating factor
Mechanical service life	approx. $3 \times 10^7$ cycles
Relay type	Electromechanical relay

Insulation characteristics: Air clearances and creepage distances between the power circuits

Insulation	Basic insulation
Overvoltage category	II
Pollution degree	3

### Electrical properties

Maximum power dissipation for nominal condition	1 W
Test voltage (Winding/contact)	5 kV <sub>rms</sub> (50 Hz, 1 min., winding/contact)
Test voltage (Changeover contact/changeover contact)	3 kV <sub>rms</sub> (50 Hz, 1 min., changeover contact/changeover contact)
Test voltage ( )	1 kV <sub>rms</sub> (50 Hz, 1 min., open contact)

Air clearances and creepage distances between the power circuits

Rated insulation voltage	250 V AC
Rated surge voltage	2.5 kV

### Input data

#### Coil side

Nominal input voltage $U_N$	120 V AC
Input voltage range	96 V AC ... 132 V AC
Mains frequency	50/60 Hz
Drive and function	monostable
Drive (polarity)	non-polarized
Typical input current at $U_N$	10 mA (50 Hz)
Input power dissipation for $U_N$	1.2 W
Typical response time	2 ms ... 15 ms
Typical release time range	5 ms ... 20 ms

# REL-FO/LRC-120AC/2X21/MS - Single relay



1308316

<https://www.phoenixcontact.com/in/products/1308316>

Protective circuit	RC element
Status display	Yellow LED
Coil resistance	6400 $\Omega$ $\pm$ 10 %

## Output data

### Switching

Contact switching type	2 changeover contacts
Type of switch contact	Single contact
Contact material	AgSnO
Maximum switching voltage	250 V AC/DC
Minimum switching voltage	5 V (10 mA)
Limiting continuous current	8 A
Maximum inrush current	16 A (20 ms, N/O contacts)
Inrush current, minimum	10 mA (5 V)
Interrupting rating (ohmic load) max.	192 W (24 V DC) 240 W (30 V DC) 2000 VA (250 V AC)

## Connection data

Connection method	FASTON connection
-------------------	-------------------

## Dimensions

Width	13 mm
Height	31.1 mm
Depth	34 mm

## Environmental and real-life conditions

### Ambient conditions

Degree of protection (Relay)	RT II (Relay)
Degree of protection (Installation location)	IP54 (Installation location)
Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C
Altitude	$\leq$ 2000 m

## Standards and regulations

Standards/regulations	IEC 61810-1 IEC 60664-1
-----------------------	----------------------------

### Air clearances and creepage distances between the power circuits

Standards/regulations	IEC 60664-1
-----------------------	-------------

## Mounting

Mounting position	any
-------------------	-----