

Eaton LSR-S11-1-I-TKG

Catalog Number: LSR-S11-1-I-TKG

Eaton LS-Titan Safety Interlock Switch, Cabinet Door Hinge Switchs, Polyamide PA66-GF25 enclosure, 6A max AC, 3A max DC, 2NC, Slow Make Break, Positive Opening, 6A at 230Vac, 0.5A at 250Vdc, Screw Terminals

General specifications



Photo is representative

Product Name	Catalog Number
Eaton LS-Titan Key interlock safety switches	LSR-S11-1-I-TKG
	UPC
	786685393834
Product Length/Depth	Product Height
1.18 in	5.98 in
Product Width	Product Weight
1.26 in	0.2063 lb
Warranty	Compliances
1 year	RoHS Compliant
Certifications	
UL Listed	

Type

LS-Titan

Contact Rating

6A at 230Vac, 0.5A at 250Vdc

Enclosure material

Polyamide PA66-GF25

Connection

Screw terminal

Contact configuration

2 NC, slow make break, positive opening

Switch type

Cabinet door hinge switch

Operating temperature - max

158 °F

Operating temperature - min

-13 °F

Environmental rating

IP66, IP67

Maximum AC current

6 A

Maximum DC current

3 A

Brochures

[LS-Titan Safety Limit Switches](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - LSR-S11-1-I-TKG](#)