

Eaton LS-S02-120AMT-ZBZ-X

Catalog Number: LS-S02-120AMT-ZBZ-X

Eaton LS-Titan Safety Interlock Switch, Cabinet Door Interlock, Polyamide PA66-GF25 enclosure, 6A max AC, 3A max DC, 2NC, Slow Make Break, Positive Opening, 6A at 240Vac, 3A at 24Vdc, Screw Terminals, 120Vac input

General specifications



Photo is representative

Product Name	Catalog Number
Eaton LS-Titan Key interlock safety switches	LS-S02-120AMT-ZBZ-X
	UPC
	786685393742
Product Length/Depth	Product Height
2.36 in	6.81 in
Product Width	Product Weight
1.21 in	0.95 lb
Warranty	Compliances
1 year	RoHS Compliant
Certifications	
UL Listed	

defaultTaxonomyAttributeLabel

Type

LS-Titan

Contact Rating

6A at 240Vac, 3A at 24Vdc

Enclosure material

Polyamide PA66-GF25

Connection

Screw terminal

Contact configuration

2 NC, slow make break, positive opening

Switch type

Cabinet door interlock

Operating temperature - max

158 °F

Operating temperature - min

-13 °F

Environmental rating

IP66, IP67

Maximum AC current

6 A

Maximum DC current

3 A

Input voltage

120 Vac

Resources

Brochures

[LS-Titan Safety Limit Switches](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - LS-S02-120AMT-ZBZ-X](#)