

# Eaton LS-S11-24DFT-ZBZ-X

Catalog Number: LS-S11-24DFT-ZBZ-X

Eaton LS-Titan Safety Interlock Switch, Cabinet Door Interlock, Polyamide PA66-GF25 enclosure, 6A max AC, 3A max DC, 1NO-1NC, Slow Make Break, Positive Opening, 6A at 240Vac, 3A at 24Vdc, Screw Terminal, 24Vdc input



## General specifications

| Product Name                              | Catalog Number       |
|-------------------------------------------|----------------------|
| Eaton LS-Titan miniature DIN limit switch | LS-S11-24DFT-ZBZ-X   |
| UPC                                       | Product Length/Depth |
| 786685393674                              | 2.36 in              |
| Product Height                            | Product Width        |
| 6.81 in                                   | 1.21 in              |
| Product Weight                            | Warranty             |
| 0.95 lb                                   | 1 year               |
| Compliances                               | Certifications       |
| RoHS Compliant                            | UL Listed            |

defaultTaxonomyAttributeLabel

Type

LS-Titan

Contact Rating

6A at 240Vac, 3A at 24Vdc

Enclosure material

Polyamide PA66-GF25

Connection

Screw terminal

Contact configuration

1 NO-1 NC, slow make break, positive opening

Switch type

Cabinet door interlock

Operating temperature - max

158 °F

Operating temperature - min

-13 °F

Environmental rating

IP66, IP67

Maximum AC current

6 A

Maximum DC current

3 A

Input voltage

24 Vdc

Resources

Brochures

[LS-Titan Safety Limit Switches](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - LS-S11-24DFT-ZBZ-X](#)