

Eaton LS-S11-24DMT-ZBZ-X

Catalog Number: LS-S11-24DMT-ZBZ-X

Eaton LS-Titan Safety Interlock Switch, Cabinet Door Interlock, Polyamide PA66-GF25 enclosure, 6A max AC, 3A max DC, 1NO-1NC, Slow Make Break, Positive Opening, 6A at 240Vac, 3A at 24Vdc, Screw Terminals, 24Vdc input



Photo is representative

General specifications

Product Name	Catalog Number
Eaton LS-Titan miniature DIN limit switch LS-S11-24DMT-ZBZ-X	
UPC	Product Length/Depth
786685393698	2.36 in
Product Height	Product Width
6.81 in	1.21 in
Product Weight	Warranty
0.95 lb	1 year
Compliances	Certifications
RoHS Compliant	UL Listed

defaultTaxonomyAttributeLabel

Type

LS-Titan

Contact Rating

6A at 240Vac, 3A at 24Vdc

Enclosure material

Polyamide PA66-GF25

Connection

Screw terminal

Contact configuration

1 NO-1 NC, slow make break, positive opening

Switch type

Cabinet door interlock

Operating temperature - max

158 °F

Operating temperature - min

-13 °F

Environmental rating

IP66, IP67

Maximum AC current

6 A

Maximum DC current

3 A

Input voltage

24 Vdc

Resources

Brochures

[LS-Titan Safety Limit Switches](#)

Catalogs

[Eaton's Volume 8—Sensing Solutions](#)

Specifications and datasheets

[Eaton Specification Sheet - LS-S11-24DMT-ZBZ-X](#)