

HC-M-12-CT-M - Contact insert module

1414354

<https://www.phoenixcontact.com/in/products/1414354>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Contact insert module, number of positions: 12, power contacts: 0, control contacts: 12, Pin, Crimp connection, 250 V, 10 A, 0.14 mm² ... 2.5 mm², application: Signal

Commercial data

Item number	1414354
Packing unit	5 pc
Minimum order quantity	5 pc
Sales key	BF7
Product key	BF7ACE
Catalog page	Page 581 (C-2-2019)
GTIN	4055626024677
Weight per piece (including packing)	9.16 g
Weight per piece (excluding packing)	8.92 g
Customs tariff number	85389099
Country of origin	PL

HC-M-12-CT-M - Contact insert module



1414354

<https://www.phoenixcontact.com/in/products/1414354>

Technical data

Notes

General	For HEAVYCON housing type B6 to B48, HC-M-B...MF... hinged module carrier frame required, CK1,6-ED... crimp contacts, crimp contacts not supplied as standard.
General	Connectors may be operated only when there is no load/voltage.

Mounting

Assembly instructions	To ensure correct use, installation in housing with IP54 protection or better is required
-----------------------	---

Product properties

Product type	Modular contact insert
Number of positions	12
Connection profile	12
Contact numbering	1 - 12
Application	Signal
Number of module slots	1
No. of power contacts	0
No. of control contacts	12
Contact material type	turned
	rolled
Series	HC-M-12

Insulation characteristics

Oversupply category	III
Degree of pollution	3

Connection data

Connection technology	
Connection technology	Crimp connection

Conductor connection

Conductor cross section	0.14 mm ² ... 2.5 mm ²
Connection cross section AWG	26 ... 14
Stripping length of the individual wire	8 mm (6 mm with 2.5 mm ²)

Dimensions

Dimensional drawing	
Width	34.2 mm

HC-M-12-CT-M - Contact insert module

1414354

<https://www.phoenixcontact.com/in/products/1414354>



Height	34 mm
Length	14.6 mm

Mechanical characteristics

Minimum housing height	52 mm
Contact diameter	1.6 mm

Electrical properties

Rated voltage (III/3)	250 V
Rated surge voltage	4 kV
Rated current	10 A

Mechanical properties

Mechanical data	
Insertion/withdrawal cycles	≥ 500

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag (alternatively Au)
Contact carrier material	PC
Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)

Standards and regulations

Testing	
Standards/regulations	PC: Fire protection in rail vehicles - requirement sets R22, R23, and R24 acc. to DIN EN 45545-2 (Risk level HL1 - HL3)

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in