

Date:	Project Name:
Type:	Part Number:



BUILT IN  
MICROWAVE SENSOR  
For some models

# SABRE SERIES

## LED LINEAR STRIP MS



## DESCRIPTION

Reno Lighting's Sabre Series is the LED Commercial Strip fixture is designed with a polycarbonate diffuser that provides impact resistance and even, low glare light. Combine this with powerful, high output LED chips, these fixtures meet today's stringent efficacy standards and bring your projects maximum energy savings.

## FEATURES

- DLC Premium for the Stairwell and Passageway Luminaires
- 0-10V dimming control compatible
- Surface or Suspension Mounting options
- Operating temperature: -22°F to +122°F (-30°C to +50°C)
- Dual Voltage 120-347V
- Easy and Safe Installation
- Integrated microwave sensor
- Frosted Polycarbonate Lens
- Suitable for Damp location
- Rated Lifetime L70(hrs): >100,000
- Includes Coverplate and V-Hangers
- Multi CCT & Wattage
- 7 year warranty

## APPLICATIONS

-  Parking Garage
-  Stairwell
-  Warehouse



**\*THE MAXIMUM HEIGHT THIS FIXTURE CAN BE MOUNTED FOR OPTIMAL SENSOR FUNCTION IS 16-17FT. IF MOUNTED ABOVE THIS HEIGHT MOTION WILL NOT BE DETECTED AS PRECISELY\***



905-604-4666



info@renolighting.com



www.renolighting.com

REV. 01/03/24

Date:	Project Name:
Type:	Part Number:

## SPECIFICATION

ORDER#	MODEL#	WATTS	VOLTAGE (V)	CCT (K)	LUMENS	EFFICACY	CRI
R33026	RENO-LSN2-22W-DV-MCCT-MS	22W	120-347V	3500K	3527 lm	160.3 lm/W	>80
				4000K	3740 lm	170 lm/W	
				5000K	3542 lm	161 lm/W	
R33020	RENO-LSN4-DV-MW-MCCT-MS	22W	120-347V	3500K	3593 lm	163.3 lm/W	>80
		28W			4544 lm	162.3 lm/W	
		36W			5807 lm	161.3 lm/W	
		44W			7053 lm	160.3 lm/W	
		22W		4000K	3806 lm	173 lm/W	>80
		28W			4816 lm	172 lm/W	
		36W			6156 lm	171 lm/W	
		44W			7480 lm	170 lm/W	
		22W		5000K	3608 lm	164 lm/W	>80
		28W			4564 lm	163 lm/W	
		36W			5832 lm	162 lm/W	
		44W			7084 lm	161 lm/W	
R33021	RENO-LSN8-DV-MW-MCCT-MS	48W	120-347V	3500K	7843 lm	163.4 lm/W	>80
		68W			11,043 lm	162.4 lm/W	
		90W			14,526 lm	161.4 lm/W	
		48W		4000K	8304 lm	173 lm/W	>80
		68W			11,696 lm	172 lm/W	
		90W			15,390 lm	171 lm/W	
		48W		5000K	7872 lm	164 lm/W	>80
		68W			11,084 lm	163 lm/W	
		90W			14,580 lm	162 lm/W	

Date:	Project Name:
Type:	Part Number:

## DLC CHART

ORDER#	MODEL#	APPLICATION	DLC	
			STANDARD	PREMIUM
R33026	RENO-LSN2-22W-DV-MCCT-MS	Direct Linear Ambient Luminaires	S-SYN41L	
		Stairwell and Passageway Luminaires		S-DRA2TN
R33020	RENO-LSN4-DV-MW-MCCT-MS	Direct Linear Ambient Luminaires	S-XJ5NO7	
		Low-Bay Luminaires for Commercial and Industrial Buildings	S-CEJ1VP	
		Stairwell and Passageway Luminaires		S-SHT7R4
R33021	RENO-LSN8-DV-MW-MCCT-MS	Direct Linear Ambient Luminaires	S-F8KWGX	
		High-Bay Luminaires for Commercial and Industrial Buildings	S-BD9243	
		Stairwell and Passageway Luminaires		S-5H2VSL

## ACCESSORIES OPTIONS

ORDER#	MODEL#	DESCRIPTION
R39501	L-BRACKET	L-Bracket for 90° Installation
R39502	I-BRACKET	I-Bracket for straight continuous Installation
R39503	RENO-LSN4-WG	LED Linear Strip Wire Guard for 4ft
R39504	RENO-LSN8-WG	LED Linear Strip Wire Guard for 8ft
R83004	RENO-EM-C08	Emergency LED Driver



L-BRACKET




RENO-LSN4-WG



RENO-EM-C08



I-BRACKET



RENO-LSN8-WG

