

# CK2,5-ED-0,5BU FE - Crimp contact



1585773

<https://www.phoenixcontact.com/in/products/1585773>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Crimp contact, contact diameter: 2.5 mm, turned, Socket, contact material: Iron, contact surface: Hard gold-plated, connection cross section: 0.5 mm<sup>2</sup> ... 0.5 mm<sup>2</sup>, AWG 20

## Commercial data

Item number	1585773
Packing unit	25 pc
Minimum order quantity	25 pc
Sales key	BF7
Product key	BF7AID
Catalog page	Page 668 (C-2-2019)
GTIN	4046356308373
Weight per piece (including packing)	1.456 g
Weight per piece (excluding packing)	0.928 g
Customs tariff number	85366990
Country of origin	DE

# CK2,5-ED-0,5BU FE - Crimp contact

1585773

<https://www.phoenixcontact.com/in/products/1585773>



## Technical data

### Notes

General	For HC-M-06, HC-M-HV, HC-M-08, HC-A, HC-BB, HC-B and HC-HV contact inserts, the quality of a crimp connection is determined by the DIN EN 60 352-2
---------	--

### Product properties

Product type	Thermal contact
Type	Individual female contact
Contact material type	turned
Series	HC-M-06; HC-M-HV; HC-M-08; HC-A; HC-BB; HC-B; HC-HV


### Electrical properties

Rated current	16 A
---------------	------

### Connection data

Connection method	Crimp connection
-------------------	------------------

### Dimensions

Dimensional drawing	
Width	4.5 mm
Height	4.5 mm
Depth	22.2 mm

### Mechanical characteristics

Contact diameter	2.5 mm
------------------	--------

### Material specifications

Contact material	Iron
Contact surface material	Hard gold-plated

### Cable/line

Stripping length of the individual wire	7.5 mm (9.5 mm at HC-M-HV...)
---	-------------------------------

### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

### Environmental and real-life conditions

#### Ambient conditions

# CK2,5-ED-0,5BU FE - Crimp contact



1585773

<https://www.phoenixcontact.com/in/products/1585773>

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

## Mounting

Assembly instructions	The quality of a crimp connection is determined by DIN EN 60352-2.
-----------------------	--

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)