

# UPS-BAT/VRLA-WTR/24DC/26AH - Battery module



2320429

<https://www.phoenixcontact.com/in/products/2320429>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Energy storage device, lead AGM, VRLA technology, 24 V DC, 26 Ah, tool-free battery replacement, automatic detection, and communication with QUINT UPS-IQ



## Product description

For continuous monitoring and intelligent management, there is constant communication with the QUINT UPS. Thanks to automatic detection of the energy storage, and tool-free switching during operation, quick installation is possible. The QUINT UPS with IQ technology energy storage leaves the warehouse fully charged.

## Your advantages

- Maximum buffer times at extreme temperatures
- Pure lead AGM technology (Absorbent Glass Mat)

## Commercial data

Item number	2320429
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CMU
Product key	CMUEW3
Catalog page	Page 338 (C-4-2019)
GTIN	4046356707718
Weight per piece (including packing)	21,460 g
Weight per piece (excluding packing)	21,460 g
Customs tariff number	85072080
Country of origin	US

# UPS-BAT/VRLA-WTR/24DC/26AH - Battery module



2320429

<https://www.phoenixcontact.com/in/products/2320429>

## Technical data

### Input data

Input voltage	24 V DC
Buffer period	120 min. (10 A)
	30 min. (40 A)

### Output data

Nominal output voltage	24 V DC
Output current $I_{\max}$	45 A
Output fuse	2x 25 A ATOF 32V
Connection in parallel	15
Connection in series	No

### Battery operation

Nominal output voltage	24 V DC
Nominal output current ( $I_N$ )	45 A

### Energy storage

End-of-charge voltage	27.6 V (20 °C)
Charging current	10.4 A
Nominal capacity	26 Ah
Latest startup date (battery only)	12 Months (0 °C ... 20 °C)
Latest startup (battery only) - range	9 Months ... 12 Months (20 °C ... 30 °C)
	6 Months ... 9 Months (30 °C ... 40 °C)
Battery technology	VRLA-WTR
Memory medium	Pure lead AGM
Accumulator type	Genesis G26EPX
Number of cells	2
Size designation	Block
Battery pack	yes
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
IQ technology	Yes
Temperature sensor	yes
Suitable for fast charging	yes
Approved according to	UL Style 3321150 °C 600 V AC 750 V DC

### Product properties

Product type	Battery unit
Product family	Battery module
Application	for QUINT4 DC-UPS, QUINT4 AC-UPS, and QUINT-UPS
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable

# UPS-BAT/VRLA-WTR/24DC/26AH - Battery module



2320429

<https://www.phoenixcontact.com/in/products/2320429>

	national regulations.
IQ technology	Yes

## Insulation characteristics

Protection class	III
Degree of pollution	2

## Dimensions

Width	358 mm
Height	174 mm
Depth	169 mm

## Mounting

Mounting position	Horizontally, on a mounting panel
-------------------	-----------------------------------

## Material specifications

Housing material	Plastic
Housing material	Metal

## Cable/line

### Battery connecting cable: A+/-

Cable cross section	6 mm <sup>2</sup>
Cable length	340 mm
Color	red/black

### Battery connecting cable: B+/-

Cable cross section	6 mm <sup>2</sup>
Cable length	110 mm
Color	red/black

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 60 °C
Max. permissible relative humidity (operation)	≤ 95 %
Shock	18 ms, 30g, in each space direction (according to IEC 60068-2-27)
Vibration (operation)	< 15 Hz, amplitude ±2,5 mm, 15 Hz ... 150 Hz, according to IEC 60068-2-6
	15 Hz ... 150 Hz, 2.3g, 90 min.

## Standards and regulations

Standard - Electrical safety	EN 62368-1/VDE 0868-1
------------------------------	-----------------------