# Eaton NON-2

## Catalog Number: NON-2

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 2 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 125 Vdc|50 kAIC at 250 Vac, Standard, 10, 250 V, 125 Vdc

#### General specifications



Eaton Bussmann series NON fuse

**UPC** 

051712300025

Product Height

0.56 in

**Product Weight** 

0.35 lb

Compliances

CE Marked

Catalog Number

NON-2

Product Length/Depth

2 in

Product Width

0.56 in

Warranty

Not Applicable



## Electrical rating

Amperage Rating

2 A

Interrupt rating

50 kAIC at 250 Vac 50 kAIC at 125 Vdc

Voltage rating

250 Vac, 125 Vdc

## Physical details

Packaging type

Standard

## General information

Class

Class H

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Quantity

10

Special features

Non current limiting

#### Resources

#### Catalogs

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - NON-2

Technical data sheets

NON-2~BUSS ONE TIME FUSE

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia