Eaton FCF60RN

Bussmann^{*}

UPS/CRITICAL

Applications

FCF60RN

Catalog Number: FCF60RN

Eaton Bussmann series FCF fuse, CUBEFuse, Finger safe, Power loss 7.27 W, Critical/UPS, 60 A, 60 Hz, 50 Hz, 1, CF, Black, Blade end, 6 min at 200%, 50 kAIC at 600 Vdc|300 kAIC at 600 V, Glass filled PES

General specifications



Eaton Bussmann series FCF fuse

UPC

051712362535

Product Height

1.9 in

Product Weight

0.17 lb

Compliances

CE Marked RoHS Compliant Catalog Number

FCF60RN

Product Length/Depth

2.13 in

Product Width

1 in

Warranty

Not Applicable

Certifications

UL Listed
CSA Certified



Electrical rating

Amperage Rating

60 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

300 kAIC at 600 Vac 50 kAIC at 600 Vdc

Response time

6 min at 200%

Voltage rating

600 Vac, 600 Vdc

Physical details

Color

Black

Fuse type

Class CF

Fast acting

Material

Glass filled PES

Number of elements

1

Operating Temperature

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH60N, CCP2-3-60CF

Resources

Catalogs

FCF60RN~Fast Acting CUBEFuse 60A Non-indication

Bussmann series complete full line catalog no. 1007

Multimedia

The Power of Space

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - FCF60RN



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2024 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia