Eaton FCF50RN

Catalog Number: FCF50RN

Eaton Bussmann series FCF fuse, 50 A, 60 Hz, 50 Hz, 1, CF, Black, Non-indicating, Electroless tin plated copper alloy terminal, Blade end, 6 min at 200%, 300 kAIC at 600 V|50 kAIC at 600 Vdc, Glass filled PES, 600 Vdc

General specifications



Eaton Bussmann series FCF fuse

Catalog Number

Product Length/Depth

FCF50RN

UPC

2.13 in

051712362528 **Product Height**

Product Width

1.9 in

Product Weight

Warranty

0.17 lb

Not Applicable

Compliances

Certifications **UL** Listed

CE Marked

RoHS Compliant

CSA Certified



Bussmann^{*}

UPS/CRITICAL



Electrical rating

Amperage Rating

50 A

Frequency rating - max

60 Hz

Frequency rating - min

50 Hz

Interrupt rating

300 kAIC at 600 Vac 50 kAIC at 600 Vdc

Response time

6 min at 200%

Voltage rating

600 Vac, 600 Vdc

Physical details

Color

Black

Fuse type

Class CF

Fast acting

Material

Glass filled PES

Number of elements

1

Operating Temperature

-40° to 80°C

Packaging type

Standard

Terminal material

Electroless tin plated copper alloy terminal

General information

Class

Class CF

Connection

Blade end

Fuse indicator

Non-indicating

Special features

Superior overload and cycling capabilities

Used with

TCFH60N, CCP2-3-60CF

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

FCF50RN~Fast Acting CUBEFuse 50A Non-indication

Multimedia

Bussmann series Fuseology

The Power of Space

Specifications and datasheets

Eaton Specification Sheet - FCF50RN



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia