

CS6364C



50 Amp, 125/250 Volt, Black & White Locking Connector, Industrial Grade

50Amp, 125/250V AC, Non-NEMA, 3P, 4W, Black & White Locking Connector, Industrial Grade, Grounding, California-Style (CS) – BLACK-WHITE

- One piece contacts reduce friction and overheating
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Ratings and NEMA I.D. permanently marked on device
- Industry exclusive limited lifetime warranty

UPC Code : 078477326213

Country Of Origin : Mexico

NEMA : Non-NEMA

Technical Information

Electrical Specifications

Amperage : 50 A

Current Interrupting : Certified for current interrupting at full rated current

Dielectric Voltage Withstand : 2000V minimum per UL 498

Grounding : Grounding

Maximum Working Voltage : 125/250V as rated

Pole : 3

Temperature Rise : Max 30°C temp rise at full-rated current after 150 cycles of OL at 150% rated DC current

Voltage : 125/250 VAC

Wire : 4

Environmental Specifications

Environment : Dry

Flammability : Rated HB or better UL94

Operating Temperature : -40° C to 75°C

Material Specifications

Assembly Screws : Brass

Cable Clamp Screw : Philips Head, SS 304

Center Pin : SS 302/304

Color : Black-White

Contact - Binding Plate : 0.100 inch thick Brass

Contact - Spring Value : 0.041 inch thick Brass

Contact Rivet : Brass

Dust Shield : Santoprene TPE

Face Module : Nylon

Mechanical Specifications

Cord Range : .680 - 1.125

Product ID : Ratings and Catalogue No. molded into face and stamped into shroud

Terminal Accom. : #10 min to #4max AWG Solid or Stranded Wire

Terminal ID : X, W, Y, Z and Green for ground

Torque Range : allen wrench to 35 inch-lbs

Ground Post : Brass
Ground Shunt : Bronze
Housing Material : Nylon
Standard Cable Clamp : Nylon
Terminal Block : 0.062inch
thick Copper
Terminal Set Screw : SS 302
/304
Wiring Chamber : Nylon

Product Features

Brand : Black and White
Color : Black-White
Device Type : Locking
Connector
NEMA : Non-NEMA

Standards and Certifications

CSA C22.2 No. 42 : File
152105
NOM : 057
RoHS : Compliant
UL 498 : File E13399
Warranty : Limited Lifetime
Warranty

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.