



Color :  Brown

UPC Code : 078477141106

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :



Gray



Ivory



Blue



Red



Black



White

5262-S

15 Amp Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Back or Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - Brown

Leviton's line of Heavy-Duty Industrial Grade Receptacles are available with a number of wiring options and features. These heavy-duty receptacles are engineered for fine appearance and top performance in demanding commercial and institutional applications using a durable, thermoplastic face and impact-resistant construction.

Technical Information

AC Horsepower Ratings

At Rated Voltage : 1/2 HP

Electrical Specifications

Amperage : 15 A

Dielectric Voltage :

Withstands 3000 V min

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Flammability : Rated V-0 per UL 94

Operating Temperature : -40° C to 75°C

Material Specifications

Body Material : PBT Polyester Blend

Color : Brown

Face Material : PBT Polyester Blend

Ground Clips : Brass

Grounding Screw : #8 Hex Head, Triple-Drive Brass

Line Contacts : 0.030" Brass

Strap Material : Steel (Galvanized G60)

Terminal Screws : #8 Triple-Drive Brass

Mechanical Specifications

Product ID : Ratings are permanently marked on the device

Product Features

Color : Brown

Device Type : Duplex Receptacle Outlet

Screw Terminal Torque : 14-18 in-lbs

Feature 4 : Smooth Face

Terminal Accom. : #14-#10 AWG

Grade : Heavy-Duty Industrial Specification Grade

NEMA : 5-15R

Terminal ID : Brass-Hot, Silver-Neutral, Green-Ground

Termination : Back and Side Wire

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File 152105

NEMA : WD-1 & WD-6

NOM : 057

UL Fed Spec WC-596 : File E13399

UL498 : File E13399

Warranty : 10-Year Limited

Patents^{*}

CA2483480

MX257790

MX321216

US6743029

US8684771

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>
JOB NUMBER: <input type="text"/>	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.