



Color : White

UPC Code : 078477141151

Country Of Origin : Mexico

NEMA :  5-20R

Available Colors :



Gray



Black



Red



Brown



Ivory



Light Almond



Blue



Orange

5362-SW

20 Amp Duplex Receptacle/Outlet, Industrial Grade, Self-Grounding

Duplex Receptacle Outlet, Heavy-Duty Industrial Specification Grade, Smooth Face, 20 Amp, 125 Volt, Back and Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - White

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

Technical Information

AC Horsepower Ratings

Electrical Specifications

At Rated Voltage : 1 HP

Amperage : 20 A

Current Limiting : Full Rated Current

Dielectric Voltage :

Withstands 2000V per UL498

Grounding : Self Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Material Specifications

Flammability : Rated V-2 per UL 94

Body Material : PBT

Operating Temperature : -40° C to 60°C

Clamp Nuts : Galvanized Steel

Face Material : PBT

Ground Clips : Brass

Grounding Screw : Steel 8-32

Line Contacts : Brass Triple-Wipe

Strap Material : Steel

Terminal Screws : Brass 10-32

Mechanical Specifications

Product Features

Product ID : Ratings are permanently marked on device

Color : White

Screw Terminal Torque : 14-18 in-lbs

Grade : Heavy-Duty Industrial Specification Grade

Terminal Accom. : 14-10 AWG NEMA : 5-20R

**Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral**

**Torque Range : 14-16 inch
pounds**

Standards and Certifications

ANSI : C-73

**CSA C22.2 No. 42 : File
152105**

NEMA : WD-1 & WD-6

NOM : 057

**UL Fed Spec WC-596 : File
E13399**

UL498 : File E13399

Warranty : 10-Year Limited

Patents*

CA2483480

MX257790

MX321216

US6743029

US8684771

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>	
JOB NUMBER: <input type="text"/>		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.