

# 2615

30 Amp, 125 Volt, Flanged Inlet Locking Receptacle, Industrial Grade

30 Amp, 125 Volt, NEMA L5-30P, 2P, 3W, Flanged Inlet Locking Receptacle, Industrial Grade, Grounding - WHITE

**ROHS Compliant** : Yes

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- 10-year limited warranty



**UPC Code** : 078477806616

**Country Of Origin** : Mexico

**NEMA** :  L5-30P

## Technical Information

### AC Horsepower Ratings

**At Rated Voltage** : 2 HP

### Electrical Specifications

**Amperage** : 30 A

**Current Limiting** : Full Rated Current

**Dielectric Voltage** :  
Withstands 2000V per UL498

**Grounding** : Grounding

**Pole** : 2

**Temperature Rise** : Max 30C  
after 250 cycles OL at 200  
percent rated current

**Voltage** : 125 VAC

**Wire** : 3

### Environmental Specifications

**Environment** : Dry

**Flammability** : Rated V-2 per  
UL 94

**Operating Temperature** : -40°  
C to 60°C

### Material Specifications

**Body Material** : Nylon

**Color** : White

**Face Material** : Nylon

**Grounding Screw** : Brass 8-32

**Line Contacts** : Solid Brass

**Strap Material** : Thermoplastic  
Nylon

**Terminal Screws** : Brass 10-32

### Mechanical Specifications

**Product ID** : Ratings and  
NEMA I.D. permanently marked  
on device

**Screw Terminal Torque** : 10-  
14 in-lbs

**Terminal Accom.** : 18-10 AWG

### Product Features

**Brand** : Black and White

**Color** : White

**Device Type** : Locking Flanged  
Inlet

**NEMA** : L5-30P

**Terminal ID** : Brass-Hot,  
Green-Ground, Silver-Neutral

**Termination** : Back

**Torque Range** : 10-14 in-lbs

Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 42** : File LR-406

**NEMA** : WD-6


**NOM** : 057

**UL Fed Spec WC-596** : File  
E13393


**UL498** : File E13393

**Warranty** : Limited Lifetime  
Warranty Warranty

**Wiring Diagram**



**Dimensional Drawing**



**SPECIFICATION SUBMITTAL**

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at:** [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.