

# 2811



Locking Plug, 30 Amp, 120/208 Volt, Industrial Grade, Black & White

30 Amp, 120/208 Volt 3-Phase Y, NEMA L21-30P, 4P, 5W, Locking Plug, Industrial Grade, Grounding - BLACK-WHITE

**ROHS Compliant** : Yes

Leviton's Black & White line of industrial grade plugs, connectors, flanged inlets, and outlets offer superior performance, long lasting reliability and features that are backed by a limited lifetime warranty:

- One piece contacts reduce friction and overheating
- Unique cord clamp accepts wide range of cord sizes
- Rugged nylon construction resists impact, sunlight, chemicals, and rough use
- Industry exclusive limited lifetime warranty

**UPC Code** : 078477808573

**Country Of Origin** : Mexico

**NEMA** :  L21-30P

## Technical Information

### Electrical Specifications

**Amperage** : 30 A

**Current Interrupting** : Certified for current interrupting at full rated current

**Dielectric Voltage** : Withstands 2000V per UL498

**Grounding** : Grounding

**Phase** : 3-Phase WYE

**Pole** : 4

**Temperature Rise** : Max 30C after 250 cycles OL at 200 percent rated current

**Voltage** : 120/208 VAC

**Wire** : 5

### Environmental Specifications

**Environment** : Dry

**Flammability** : Rated HB or better UL94

**Operating Temperature** : -40° C to 60°C

### Material Specifications

**Assembly Screws** : Steel, Zinc Plated

**Back Cover** : Thermoplastic

**Blades/Contacts** : Solid Brass

**Body Material** : Impact Modified Nylon

**Clamp Insert** : Nylon

**Color** : Black-White

**Cord-Clamp** : Nylon

### Mechanical Specifications

**At Rated Voltage** : 3 HP

**Cord Range** : .595 - 1.150

**Product ID** : Ratings are permanently marked on device

**Terminal Accom.** : 18-10 AWG

**Terminal ID** : Brass-Hot, Green-Ground, Silver-Neutral

**Torque Range** : 10-14 in-lbs

**Wire Gauge** : 14-8 AWG

**Terminal Screws** : Brass

**Wire Module** : Nylon

Product Features

**Brand** : Black and White

**Color** : Black-White

**Device Type** : Locking Plug

**NEMA** : L21-30P

Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 42** : File LR-406


**NOM** : 057

**UL Fed Spec WC-596** : File E13393

**UL498** : File E13393

**Warranty** : Limited Lifetime  
Warranty Warranty

## Wiring Diagram



### SPECIFICATION SUBMITTAL

|                                            |                                                 |
|--------------------------------------------|-------------------------------------------------|
| <b>JOB NAME:</b><br><input type="text"/>   | <b>CATALOG NUMBERS:</b><br><input type="text"/> |
| <b>JOB NUMBER:</b><br><input type="text"/> | <input type="text"/>                            |

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at:** [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.