



16241-W



Color : White

UPC Code : 078477473160

Country Of Origin : Please Contact Customer Service

NEMA : 5-15R

Available Colors :



Ivory

15 Amp Decora Plus Single Receptacle/Outlet, Commercial Grade, Self-Grounding

Decora Plus Single Receptacle Outlet, Commercial Specification Grade, Smooth Face, 15 Amp, 125 Volt, Side Wire, NEMA 5-15R, 2-Pole, 3-Wire, Self-Grounding - White

ROHS Compliant : Yes

Leviton's line of Heavy-Duty Specification Grade receptacles are designed and manufactured to withstand the most demanding environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, etc., these Commercial Grade devices are the electrical contractor's choice for use in hotels, schools, hospitals and commercial office buildings.

Technical Information

AC Horsepower Ratings

Electrical Specifications

At Rated Voltage : 1/2 HP

Amperage : 15 A

Current Limiting : Full Rated Current

Dielectric Voltage :
Withstands 2000V per UL498

Grounding : Self-Grounding

Pole : 2

Temperature Rise : Max 30C after 250 cycles OL at 200 percent rated current

Voltage : 125 VAC

Wire : 3

Environmental Specifications

Material Specifications

Flammability : Rated V-2 per UL 94

Body Material : Thermoplastic Nylon

Operating Temperature : -40° C to 60°C

Clamp Nuts : Zinc-Plated Steel

Color : White

Face Material : Thermoplastic Nylon

Ground Clips : Brass-Plated

Grounding Screw : Brass 8-32

Line Contacts : Brass Triple-Wipe .031 Thick

Strap Material : Zinc-Plated Steel

Terminal Screws : Brass 10-32

Mechanical Specifications

Product ID : Ratings are permanently marked on device
Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Termination : Side Wire

Product Features

Brand : Decora Plus

Color : White

Device Type : Single Receptacle Outlet

Feature 4 : Smooth Face

Grade : Commercial Specification Grade

NEMA : 5-15R

Standards and Certifications

ANSI : C-73

NEMA : WD-6


NOM : 057

UL498 : File E13399

Warranty : 10-Year Limited

Dimensional Drawing

Wiring Diagram



5-15R

SPECIFICATION SUBMITTAL

| | |
|-------------------------------------|---|
| JOB NAME: <input type="text"/> | CATALOG NUMBERS: <input type="text"/> <input type="text"/> |
| JOB NUMBER: <input type="text"/> | <input type="text"/> <input type="text"/> |

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.