



Color: White

UPC Code: 078477055199

Country Of Origin: Mexico

NEMA : 5-15R

Available Colors:



8259-V

15 Amp, 125 Volt, Straight Blade Connector, Hospital Grade

15 Amp, 125 Volt, NEMA 5-15R, 2P, 3W, Connector, Straight Blade, Hospital Grade, Grounding, Python - White

When it comes to the demanding nature of today's commercial and industrial electrical environments, ruggedness and ease of installation are the features you look for first in any line of plugs and connectors. Leviton's Python straight-blade plugs and connectors hold up under the most exacting requirements, the toughest conditions, the roughest handling. Python's exceptional design features meet your needs for a quick, easy-to-wire plug and connector system, a must in today's faced-paced world where lost minutes on a job can translate into lost profits.

Technical Information

<u>Electrical Specifications</u> <u>Environmental Specifications</u>

Amperage: 15 A Environment: Dry

Current Interrupting : Certified for current interrupting at full UL 94
rated current

Operating Temperature : -40°
Dielectric Voltage : C to 60°C

Withstands 2000V per UL498

 $\textbf{Grounding}: \mathsf{Grounding}$

Pole: 2

Temperature Rise: Max 30C after 250 cycles OL at 200 percent rated current

Voltage: 125 VAC

Wire: 3

Material Specifications Mechanical Specifications

Product ID: Ratings and

Terminal ID: Brass-Hot,

on device

NEMA I.D. permanently marked

Terminal Accom.: 18-10 AWG

Green-Ground, White-Neutral

Assembly Screws: Steel, Zinc Cord Range: .245 - .700

Plated

Back Cover: Thermoplastic

Blades/Contacts: Solid Brass

Body Material: Super Tough

Nylon

Clamp Insert: Nylon

Color: White

Cord-Clamp: Nylon

Terminal Screws: Brass

Wire Module: Nylon

Product Features Standards and Certifications

Brand: Python ANSI: C-73

Color: White CSA C22.2 No. 42: File LR-406

Device Type : Straight Blade

Connector

Grade: Hospital

NEMA: 5-15R

NEMA: WD-6

NOM: 057


UL 498: File E13399

UL Fed Spec WC-596: File

E13393

Warranty: 2-Year Limited

Wiring Diagram



5-15R

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.