



Color :  Brown

UPC Code : 06867911923

Country Of Origin : Please Contact Customer Service

Available Colors :



18201-CB

Single-Pole Toggle Switch, Commercial Specification Grade, Framed, Canadian, 15 Amp, 347 Volt AC, Side Wire, Brown

Technical Information

Electrical Specifications

Amperage : 15 A

Dielectric Voltage :
Withstands 1500V for 1 minute

Endurance : 50,000 cycles minimum

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 65°C

Overload UL20 Test : 100 cycles of OL at 4.8 times rated current

Temperature Rise : Maximum 30 degrees C rise

Voltage : 347 VAC

Environmental Specifications

Base Material : Thermoplastic

Contact Material : Silver Alloy

Cover Material : Thermoplastic

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 65°C

Strap Material : Steel

Terminal Screws : Brass 8-32

Toggle : Polycarbonate

Voltage : 347 VAC

Material Specifications

Base Material : Thermoplastic

Contact Material : Silver Alloy

Cover Material : Thermoplastic

Product ID : Ratings are permanently marked on device

Strap Material : Steel

Terminal Accom. : 14-#10 AWG back wired; #14-#12 AWG side wired

Terminal ID : Brass-Hot (If Applicable) Black-Hot White-Neutral Green-Gnd

Terminal Screws : Brass 8-32

Termination : Side Wire

Toggle : Polycarbonate

Torque Range : 12-14 inch pounds

Mechanical Specifications

Color : Brown

Device Type : Toggle Switch

Feature 3 : Framed

Feature 4 : Canadian

Function : Single-Pole

Grade : Commercial Specification Grade

Product ID : Ratings are permanently marked on device

Terminal Accom. : 14-#10 AWG back wired; #14-#12 AWG side wired

Terminal ID : Brass-Hot (If Applicable) Black-Hot White-Neutral Green-Gnd

Termination : Side Wire

Torque Range : 12-14 inch pounds

Voltage : 347 VAC

Product Features

ANSI : C-73

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 111 : File
#152105

Color : Brown

Device Type : Toggle Switch

Feature 3 : Framed

Feature 4 : Canadian

Function : Single-Pole

Grade : Commercial
Specification Grade

UL Fed Spec WS896E : File
#E7458

UL Standard : UL20

Amperage : 15 A

CSA C22.2 No. 111 : File
#152105

Dielectric Voltage :
Withstands 1500V for 1 minute

Endurance : 50,000 cycles
minimum

Overload UL20 Test : 100
cycles of OL at 4.8 times rated
current

Standards and Certifications
: UL/CSA

Temperature Rise : Maximum
30 degrees C rise

UL Fed Spec WS896E : File
#E7458

UL Standard : UL20

Voltage : 347 VAC

Warranty

Warranty : 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: 	
JOB NUMBER: 		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.