

5691-CW

Decora Plus Single-Pole Rocker Switch, Commercial
Specification Grade, Canadian, 15 Amp, 347 Volt AC, Back or
Side Wire, Self-Grounding - White



UPC Code : 06867918065

Country Of Origin : Please Contact
Customer Service

Available Colors :



Technical Information

Electrical Specifications

Actuator Material :
Thermoplastic

Amperage : 15 A

Body Material : Thermoplastic

Dielectric Voltage :
Withstands 1500V for 1 minute

Endurance : 50,000 cycles
minimum

Grounding : Self-Grounding

Overload UL20 Test : 100
cycles of OL at 4.8 times rated
current

Strap Material : Steel

Temperature Rise : Maximum
30 degrees C rise

Voltage : 347 VAC

Environmental Specifications

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 65°C

Product ID : Stamped on Strap

Terminal Accom. : 14-#10
AWG back wired; #14-#12
AWG side wired

Terminal ID : Brass-Hot (If
Applicable) Black-Hot White-
Neutral Green-Gnd

Termination : Back or Side
Wire

Material Specifications

Actuator Material :
Thermoplastic

Body Material : Thermoplastic

Brand : Decora Plus

Device Type : Rocker Switch

Feature 4 : Canadian

Function : Single-Pole

Grade : Commercial
Specification Grade

Strap Material : Steel

Mechanical Specifications

Product ID : Stamped on Strap

Screw Terminal Torque : 14-
18 in-lbs

Terminal Accom. : 14-#10
AWG back wired; #14-#12
AWG side wired

Terminal ID : Brass-Hot (If
Applicable) Black-Hot White-
Neutral Green-Gnd

Termination : Back or Side
Wire

Product Features

Brand : Decora Plus

Device Type : Rocker Switch

Feature 4 : Canadian

Function : Single-Pole

Grade : Commercial
Specification Grade

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 111 : File
#152105

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 65°C

Warranty

Amperage : 15 A

Dielectric Voltage :

Withstands 1500V for 1 minute

Endurance : 50,000 cycles
minimum

Grounding : Self-Grounding

Overload UL20 Test : 100
cycles of OL at 4.8 times rated
current

Temperature Rise : Maximum
30 degrees C rise

Voltage : 347 VAC

Warranty : 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS:
JOB NUMBER: 	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.