



5693-CW

Decora Plus 3-Way Rocker Switch, Commercial Specification Grade, Canadian, 15 Amp, 347 Volt AC, Back or Side Wire, Self-Grounding - White

Technical Information

Electrical Specifications

Actuator Material :
Thermoplastic

Amperage : 15 A

Body Material : Thermoplastic

Dielectric Voltage :
Withstands 1500V for 1 minute

Endurance : 50,000 cycles minimum

Grounding : Self-Grounding

Overload UL20 Test : 100 cycles of OL at 4.8 times rated current

Strap Material : Steel

Temperature Rise : Maximum 30 degrees C rise

Voltage : 347 VAC

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 65°C

Product ID : Stamped on Strap

Terminal Accom. : 14-#10 AWG back wired; #14-#12 AWG side wired

Terminal ID : Brass-Hot (If Applicable) Black-Hot White-Neutral Green-Gnd

Termination : Back or Side Wire

Material Specifications

Actuator Material :
Thermoplastic

Body Material : Thermoplastic

Brand : Decora Plus

Device Type : Rocker Switch

Feature 4 : Canadian

Function : 3-Way

Grade : Commercial Specification Grade

Strap Material : Steel

Mechanical Specifications

Product ID : Stamped on Strap

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-#10 AWG back wired; #14-#12 AWG side wired

Terminal ID : Brass-Hot (If Applicable) Black-Hot White-Neutral Green-Gnd

Termination : Back or Side Wire

Product Features

Brand : Decora Plus

Device Type : Rocker Switch

Feature 4 : Canadian

Function : 3-Way

Grade : Commercial Specification Grade

Standards and Certifications

ANSI : C-73

Amperage : 15 A

CSA C22.2 No. 111 : File #152105

Dielectric Voltage :
Withstands 1500V for 1 minute

UPC Code : 06867918075

Country Of Origin : Please Contact Customer Service

Available Colors :



Gray



Ivory

Endurance : 50,000 cycles
minimum

Grounding : Self-Grounding

Overload UL20 Test : 100
cycles of OL at 4.8 times rated
current

Temperature Rise : Maximum
30 degrees C rise

Voltage : 347 VAC

Warranty

Flammability : Rated V-2 per
UL 94

Operating Temperature : -40°
C to 65°C

Warranty : 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:		
JOB NUMBER:		
CATALOG NUMBERS:		

Leviton Manufacturing Co., Inc
201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com
© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.
If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.