



UPC Code : 078477332559

Country Of Origin : China

E5325-W

Decora Edge 15 Amp Tamper-Resistant Duplex Outlet, White

15 Amp, 125 Volt, NEMA: 5-15R, 2 Pole, 3-Wire, Straight Blade, Decora Duplex Tamper-Resistant Outlet, Self-grounding, UL /CSA, NEC compliant - White

ROHS Compliant : Yes

- **FASTER** – Patent-pending lever terminals for fast, efficient wiring. As Easy as PUSH. CLICK. DONE
- **EASIER** – Large strap makes installations easier as well as the ability to use 14 gauge and 12 gauge stranded and solid copper wire
- **SAFER** – No exposed metal parts for enhanced safety
- **CONVENIENT** – Color-coded lever terminals to help prevent miswiring
- **COMPATIBLE** – Coordinates seamlessly with other Decora devices and can be used with any sized Decora wallplate

Available only in USA. Available in Canada starting in August 2023

Technical Information

Electrical Specifications

Amperage : 15 A

Grounding : Self-grounding

Pole : 2

Wire : 3

Mechanical Specifications

Terminal Accom. : Side Lever Wire #14-#12 AWG; Stranded and Solid Copper wire only

Terminal ID : Color Coded Lever Terminals, including Ground

Termination : Side Lever

Product Features

Amperage : 15 A

Color : White

Device Type : Decora Duplex Receptacle

Standards and Certifications

CSA : C22.2 No. 42: File 152105; Class 6233-01

NEMA Rating : 5-15R

NOM : NOM Certified

UL 498 : File E13399

Warranty

Warranty : 2-Year Limited

Features and Benefits

- Provides the traditional appearance and superior performance of Decora® devices in a new, faster, easier-to-install, and safer design
- Patent pending lever terminals for fast, efficient wiring
- Color-coded lever terminals reduces risk of miswiring

- Lever doors have snap feature to assure connection has been made; audible click confirms lever door is closed
- Only Residential device on the market with a quick termination ground wire
- No exposed metal parts for enhanced safety; eliminates need for electrical tape
- Strap's unique tongue and groove alignment offers quicker trim out on multi-gang installations
- Lever connectors work with 14 gauge and 12 gauge stranded and solid copper wire
- Wire openings prevent wire insulation from being inserted into the terminals
- One standard strip gauge for all devices
- Devices coordinate seamlessly with other Decora devices
- Longer and wider strap is compatible with Midway wallplates, and with Standard sized wallplates when breakaway tab is removed
- Can be used with Decora wallplates and Decora Plus™ screwless wallplates
- Outlet allows for split circuit applications
- Outlet is Tamper-Resistant to help prevent access by most non-rated/foreign objects

Patents *

CA2621644	CA2624409
US7355117	US7820909
US8242362	

This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS: <table border="1" style="width: 100%;"> <tbody> <tr> <td style="width: 50%; height: 20px;"> </td> <td style="width: 50%; height: 20px;"> </td> </tr> <tr> <td style="height: 20px;"> </td> <td style="height: 20px;"> </td> </tr> </tbody> </table>				
JOB NUMBER: 					

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.