

**PRODUCT CODE: CL108P-115WM-PF5C9N**
**8 INCH APERTURE CLOSET LIGHT SURFACE MOUNT 5CCT**


1-3/10" (33 mm)

7.8" (198 mm)



## PRODUCT DESCRIPTION

The new Etlin-Daniels Low profile LED Closet Light CL108P-115WM-PF5C9N offers compact design, enhanced energy savings, glare free illumination, all with a built-in PIR Sensor. The aluminum housing will dissipate what little heat the diode array produces and the easy-to-remove frosted polycarbonate lens allows for simply, quick installation.

This new generation is equipped with a 5CCT switch allowing for a choice between 5 available color temperatures and is now 90CRI for enhanced color definition. The CL108P comes with multiple keyless slot locations to attach to the j-box, providing optimal Sensor positioning for its auto on/off function. Once the space is vacated, the sensor will automatically shut off the fixture in 30 seconds.

The new generation CL108P is the perfect solution to illuminate closets, garbage rooms, small storage rooms, washrooms, basements, residential garages - anywhere a lighting fixture may be left on when the space is vacated.

## FEATURES

- LED Indoor Light Source
- Surface Mount low profile 1-1/3" deep housing // 8" diameter
- Durable aluminum body with frosted polycarbonate lens.
- 120V
- 90CRI
- 5CCT - 2700K/3000K/3500K/4000K/5000K
- Wet location rated
- Keyless slot mounting to j-box
- PIR Sensor built-in - 30 seconds to off when space is vacated
- 5 year warranty
- L70 - 50,000 hours
- Energy Star Certified

## PRODUCT SPECIFICATIONS (OPTICAL DATA)

## PRODUCT SPECIFICATIONS (ELECTRICAL DATA)

SYSTEM EFFICACY	LUMENS	COLOR TEMPERATURE	CRI	VOLTAGE	POWER FREQ.
2700K = 60.53LM/W 3000K = 62.86LM/W 3500K = 65.4LM/W 4000K = 61.2LM/W 5000K = 57.2LM/W	2700K = 908 LM 3000K = 942.9 LM 3500K = 987.21 LM 4000K = 918.1 LM 5000K = 858.1 LM	CHANGEABLE: 2700K / 3000K 3500K / 4000K / 5000K	>90CRI	120VAC	60HZ

## PRODUCT SPECIFICATIONS

WATTAGE	FIXTURE MATERIAL	LIFE SPAN	PRODUCT DIMENSIONS	CARTON SIZE	
15W	PC PLASTIC / METAL	>50,000 HOURS	7.8 x 1 INCHES (198 x 33 MM)	6.125 X 6.125 X 1.375 INCHES (155 X 155 X 35 MM)	

## ADDITIONAL INFORMATION

### INSTALLATION METHOD

CEILING MOUNT

### FIXTURE COLOR/DIFFUSER

WHITE MATTE / FROSTED

### CONTROL TYPE

 NON-DIMMABLE  
PIR SENSOR

CATALOG #		TYPE
PROJECT		DATE
PREPARED BY		

**PRODUCT CODE: CL108P-115WM-PF5C9N**
**8 INCH APERTURE CLOSET LIGHT SURFACE MOUNT 5CCT**
**CERTIFICATIONS**

**CAN ICES-005 (B) / NMB-005 (B)**
**CONTROL**

**ORDERING INFORMATION - CL SERIES**

SERIES	SIZE	CONTROL TYPE	VOLTAGE	WATTAGE	FINISH	DIFFUSER	COLOR TEMPERATURE	CRI	DIMMABLE
E.G. <b>CL10</b>	<b>8</b>	<b>P</b>	<b>1</b>	<b>15</b>	<b>WM</b>	<b>PF</b>	<b>5C</b>	<b>9</b>	<b>N</b>
<b>CL10 - CLOSET LIGHT</b>	<b>8 - 8 INCH</b>	<b>P = PIR SENSOR</b>	<b>1-120V</b>	<b>15-15W</b>	<b>WH-WHITE MATTE</b>	<b>PF - PC FROSTED</b>	<b>C = 5CCT</b>	<b>90 = CRI &gt;90</b>	<b>N = NO</b>
							<b>COLOR CHANGEABLE:</b>		
							<b>2700K/3000K/3500K</b>		
							<b>4000K/5000K</b>		

**Head Office** - 1850 Wilson Ave. · Toronto, ON · M9M 1A1 · **Tel:** 416.741.7336 · **Fax:** 416.741.9104

**Toll Free:** in Canada. 1.800.661.9610 · in USA. 1.888.762.5384 (SOCKETS4U)

[www.etlin-daniels.com](http://www.etlin-daniels.com) · For sales/service questions - [sales@etlin.com](mailto:sales@etlin.com)