



Pulse Start Metal Halide Standard

MS400/BU/ED28/PS 12PK

Philips Pulse Start Metal Halide Lamps offer an optimized metal halide system for greater efficiency and lumen maintenance.

Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA:21 CFR 1040.30 Canada: SOR/DORS/80-381)

Product data

General Information	
Cap-Base	E39 [Single Contact Mogul Screw]
Operating Position	H15 [Hanging +/-15D or Base Up (BU)]
Life to 50% Failures (Nom)	20,000 hour(s)
Light Technical	
Color Code	640 [CCT of 4000K]
Luminous Efficacy (rated) (Nom)	110 lm/W
Color Designation	Cool White (CW)
Chromaticity Coordinate X (Nom)	385
Chromaticity Coordinate Y (Nom)	390
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (Rated) (Min)	105 lm/W
Color rendering index (CRI)	68


Operating and Electrical	
Lamp Current (Nom)	3.2 A
Voltage (Nom)	135 V
Mechanical and Housing	
Bulb Finish	Clear
Bulb Material	Hard Glass
Bulb Shape	ED28
Approval and Application	
Mercury (Hg) Content (Nom)	50 mg
Product Data	
Order product name	PS MH Std 400W/640 CW Mog ED28 1SL
Full product name	MS400/BU/ED28/PS 12PK
Order code	232520

Pulse Start Metal Halide Standard

Material Nr. (12NC)	928601165501
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.001 kg
EAN/UPC - Product/Case	046677232528

Numerator - Packs per outer box	12
EAN/UPC - Case	50046677232523

Dimensional drawing



Product	D	C (max)
PS MH Std 400W/640 CW Mog ED28 1SL	3.5 inch	8.3 inch

