HUBBELL Wiring Device-Kellems

TradeSelect, Straight Blade Devices, Residential Grade, Receptacles, Tamper Resistant Duplex, 15A 125V, 2- Pole 3-Wire Grounding, 5-15R

By Hubbell Wiring Device-Kellems Catalog # RR15SWTR

TradeSelect, Straight Blade Devices, Residential Grade, Receptacles, Tamper Resistant Duplex, 15A 125V, 2- Pole 3-Wire Grounding, 5-15R, Self Grounding, White.



- Smooth indented face appearance
- Multiple-drive Slot/Phillips/Robertson head screws
- Tough thermoplastic ultrasonically welded cover and base

General

Application

Catalog Number RR15SWTR
Color White
Blanc

EU RoHS Indicator Yes

Environmental Conditions

Item TypeTraditional DuplexMaterialThermoplasticMaterial - Mounting HardwareScrew Mounting

Number Of Poles 2-Pole

Performance Environmental - Operating

temperature - -20°C to 60°C

Mechanical - Terminal -Terminal screws accepts up to #12 AWG, Push wire designed

for #14 AWG solid copper wire

only

UPC 883778301544

Dimensions

Display Size Standard Sized Product

Electrical Ratings

Amperage Rating 15 A

Connectivity Push and Side Wire

Current / Amperage Rating 15 A
Current Rating 15 A

Phase Single Phase
Voltage Rating 125 VAC
Voltage Rating Description 125 VAC
Wattage 1875



Conductor Related

Number Of Wires 3-Wire Grounding
Wire Size #14 AWG to #12 AWG

Certifications And Compliance

Nema Rating 5-15R Standards - RoHS Compliance CM

Status

Logistics

Carton Quantity 10
Pallet Quantity 9000

Product Assets

Catalog Page - WDK Z-16 Catalog Page Catalogs - WDK Catalog Full 2024

Engineering Drawing - RR15SWTR AutoCAD Drawing

Literature - Residential Catalog

Literature - Residential Product Guide

Literature - Tamper-Resistant Receptacles for Residential

Applications

Literature - Tamper-Resistant Receptacles

Sales Drawings - WDK_RR15STR_DRAWING_PDF

Warranty - tradeSELECT $\!\!\!^{\text{\tiny{M}}}$ and netSELECT $\!\!\!^{\text{\tiny{R}}}$

Video - Tamper-Resistant Receptacles

Video - Tradeselect Devices

