

2024 Specification Sheet - English

**LONG DESCRIPTION –**

Long Description Marketing Copy

Strong, welded steel framesForged steel closure-type hooks with 1 IN (25.4 mm) opening. 5 IN (127 mm) wide aluminum alloy sheaves with self-lubricating bearings. Select a sheave with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force

PRODUCT NAME –

Page Title

24" Hook-Type Sheave

PRODUCT OVERVIEW –

Marketing Text 1

Strong, welded steel framesForged steel closure-type hooks with 1 IN (25.4 mm) opening

Marketing Text 2

5 IN (127 mm) wide aluminum alloy sheaves with self-lubricating bearings

Marketing Text 3

Select a sheave with a maximum rated capacity that meets or exceeds the cable puller's maximum pulling force

PRODUCT SPECIFICATION –

Product Specification 1

Keyway : None

Product Specification 2

Outside Diameter : 24"

Product Specification 3

Pitch Diameter : Between 24" and 19.5"

Product Specification 4

Groove : R2.25"

Product Specification 5

Material : 5 IN (127 mm) wide aluminum alloy sheaves with self-lubricating bearings

Product Specification 6

Includes : 16797 UPC 16797 Sheave Pin, 50302 UPC 50302 Sheave Pin Clip(2), 15363 UPC 15363 Sheave, 16798 UPC 16798 Sheave Bushing(2), 16802 UPC 16802 Yoke Frame

Product Specification 7

Standard : SHEAVE-CABLE 24" HOOK TYPE

Product Specification 8

Type : Sheave Assembly

Product Specification 9

Application : Electrical Cable pull

Product Specification 10

Capacity : 4000.000 LB (17.800 KN)