


G fuse link DIN 41660 quick-response High breaking capacity Rated continuous current 1 A



| Model                                      |                    |             |
|--------------------------------------------|--------------------|-------------|
| product brand name                         | SETRON             |             |
| product designation                        | G fuse link        |             |
| design of the product                      | quick-response (F) |             |
| type of miniature fuse                     | ceramic fuse       |             |
| General technical data                     |                    |             |
| size of the fuse link                      | 5 x 20 mm          |             |
| melting characteristics                    | quick acting (F)   |             |
| type of voltage of the operating voltage   | AC                 |             |
| operating voltage rated value              | 250 V              |             |
| Main circuit                               |                    |             |
| operational current rated value            | 1 A                |             |
| Display and operation                      |                    |             |
| product component visual defect indication | No                 |             |
| Mechanical Design                          |                    |             |
| net weight                                 | 1 g                |             |
| Approvals Certificates                     |                    |             |
| General Product Approval                   | other              | Environment |



[Confirmation](#)



[Confirmation](#)

[Miscellaneous](#)

[Environmental Con-  
firmations](#)

Environment

[Environmental Con-  
firmations](#)

| Further information                                                                                                                                                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Information on the packaging<br><a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a>                                                                                          |
| Information- and Downloadcenter (Catalogs, Brochures,...)<br><a href="http://www.siemens.com/lowvoltage/catalogs">http://www.siemens.com/lowvoltage/catalogs</a>                                                                                                 |
| Industry Mall (Online ordering system)<br><a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1822-7EF16">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1822-7EF16</a>                                          |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,...)<br><a href="https://support.industry.siemens.com/cs/ww/en/ps/8WA1822-7EF16">https://support.industry.siemens.com/cs/ww/en/ps/8WA1822-7EF16</a>                                                |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)<br><a href="http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1822-7EF16">http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1822-7EF16</a> |

---

last modified: 1/14/2024 

