

Siemens  
EcoTech



Selector switch, illuminable, 22 mm, round, metal, shiny, white, selector switch, long, 3 switch positions I>O<II, momentary contact on the left, latching on the right, actuating angle 2x45°, 10:30h/12h/13:30h



|                                                    |                                                                                            |
|----------------------------------------------------|--------------------------------------------------------------------------------------------|
| product brand name                                 | SIRIUS ACT                                                                                 |
| product designation                                | Selector switches                                                                          |
| design of the product                              | Actuating/signaling element                                                                |
| product type designation                           | 3SU1                                                                                       |
| product line                                       | Metal, shiny, 22 mm                                                                        |
| Enclosure                                          |                                                                                            |
| number of command points                           | 1                                                                                          |
| Actuator                                           |                                                                                            |
| design of the actuating element                    | selector, long                                                                             |
| principle of operation of the actuating element    | momentary contact/latching, 2x45° (10:30 h/12 h/13:30 h), return from left, right latching |
| product extension optional                         |                                                                                            |
| • light source                                     | Yes                                                                                        |
| • contact module                                   | Yes                                                                                        |
| color of the actuating element                     | white                                                                                      |
| material of the actuating element                  | plastic                                                                                    |
| shape of the actuating element                     | Handle                                                                                     |
| outer diameter of the actuating element            | 44.8 mm                                                                                    |
| number of switching positions                      | 3                                                                                          |
| actuating angle                                    |                                                                                            |
| • clockwise                                        | 45°                                                                                        |
| • anticlockwise                                    | 45°                                                                                        |
| Front ring                                         |                                                                                            |
| product component front ring                       | Yes                                                                                        |
| design of the front ring                           | standard                                                                                   |
| material of the front ring                         | Metal, high gloss                                                                          |
| color of the front ring                            | silver                                                                                     |
| General technical data                             |                                                                                            |
| protection class IP                                | IP66, IP67, IP69(IP69K)                                                                    |
| degree of protection NEMA rating                   | 1, 2, 3, 3R, 4, 4X, 12, 13                                                                 |
| shock resistance                                   |                                                                                            |
| • according to IEC 60068-2-27                      | sinusoidal half-wave 15g / 11 ms                                                           |
| vibration resistance                               |                                                                                            |
| • according to IEC 60068-2-6                       | 10 ... 500 Hz: 5g                                                                          |
| operating frequency maximum                        | 1 800 1/h                                                                                  |
| mechanical service life (operating cycles) typical | 1 000 000                                                                                  |
| reference code according to IEC 81346-2            | S                                                                                          |

|                                                                         |                                                                    |
|-------------------------------------------------------------------------|--------------------------------------------------------------------|
| Substance Prohibittance (Date)                                          | 10/01/2014                                                         |
| <b>Safety related data</b>                                              |                                                                    |
| proportion of dangerous failures                                        |                                                                    |
| • with low demand rate according to SN 31920                            | 20 %                                                               |
| • with high demand rate according to SN 31920                           | 20 %                                                               |
| <b>B10 value with high demand rate according to SN 31920</b>            | 300 000                                                            |
| <b>failure rate [FIT] with low demand rate according to SN 31920</b>    | 100 FIT                                                            |
| <b>IEC 61508</b>                                                        |                                                                    |
| T1 value for proof test interval or service life according to IEC 61508 | 20 a                                                               |
| <b>Ambient conditions</b>                                               |                                                                    |
| ambient temperature                                                     |                                                                    |
| • during operation                                                      | -25 ... +70 °C                                                     |
| • during storage                                                        | -40 ... +80 °C                                                     |
| environmental category during operation according to IEC 60721          | 3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 ... 95%) |
| <b>Environmental footprint</b>                                          |                                                                    |
| Environmental Product Declaration (EPD)                                 | Yes                                                                |
| Global Warming Potential [CO2 eq] total                                 | 0.593 kg                                                           |
| Global Warming Potential [CO2 eq] during manufacturing                  | 0.625 kg                                                           |
| Global Warming Potential [CO2 eq] during operation                      | 0.235 kg                                                           |
| Global Warming Potential [CO2 eq] after end of life                     | -0.267 kg                                                          |
| Siemens Eco Profile (SEP)                                               | Siemens EcoTech                                                    |
| <b>Installation/ mounting/ dimensions</b>                               |                                                                    |
| height                                                                  | 44.8 mm                                                            |
| width                                                                   | 44.8 mm                                                            |
| shape of the installation opening                                       | round                                                              |
| mounting diameter                                                       | 22.3 mm                                                            |
| positive tolerance of installation diameter                             | 0.4 mm                                                             |
| mounting height                                                         | 28.8 mm                                                            |
| installation width                                                      | 44.8 mm                                                            |
| installation depth                                                      | 25.4 mm                                                            |
| <b>Approvals Certificates</b>                                           |                                                                    |
| General Product Approval                                                | Test Certificates                                                  |



[Confirmation](#)



[Type Test Certificates/Test Report](#)

|                   |       |             |
|-------------------|-------|-------------|
| Test Certificates | other | Environment |
|-------------------|-------|-------------|

[Special Test Certificate](#)

[Confirmation](#)



Siemens  
EcoTech



[Environmental Confirmations](#)

#### Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1052-2CP60-0AA0>

Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1052-2CP60-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1052-2CP60-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1052-2CP60-0AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1052-2CP60-0AA0&lang=en)



---

last modified:

2/6/2024 