

PROVO PART NUMBER
92225

MULTI-CONDUCTOR • FOIL SHIELD
STRANDED TINNED COPPER CONDUCTORS
CONDUCTORS TWISTED • PVC INSULATION
100% ALUMINUM FOIL SHIELD
STRANDED TINNED COPPER DRAIN WIRE
PVC JACKET • -20°C +105°C



SPEC CRITERIA	SPECIFICATION
AWG	20
STRANDING	7 x 28
NUMBER OF CONDUCTORS	3
DRAIN WIRE AWG	22
INSULATION TYPE	PVC
INSULATION THICKNESS	0.010
JACKET TYPE	PVC
JACKET THICKNESS	0.023
NOM. CABLE OD	0.176
VOLTAGE	600
TEMPERATURE	-20°C to +105°C
PUT-UP METERS	300 / 150
WEIGHT (LBS)	28 / 14
CSA	AWM, CMG, FT-4
UL	CMG, UL444
RoHS	COMPLIANT
FLAME TEST	FT-4
COLOUR CODE	Black / White / Red

©2022 PROVO LTD.

Provo makes every reasonable effort to ensure their accuracy at the time of this publication. Information and specifications herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. The information provided is correct to the best of Provo's knowledge, and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes part of. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. All sales of Provo products are subject to Provo's standard terms and conditions of sale.