



Series-A

Primary Voltage Secondary Voltage			600/480 120 x 240	575/460 115 x 230	550/440 110 x 220	  		60 Hertz		
VA Rating	CE VA Rating	Catalog Number	Output Amps	Overall Dimensions			Mounting Centers		Mounting Slot	Approx. Ship Weight Lbs.
				A	B	C	D	E	G X H	
50	50	DCE50UH	0,42/0,21	2,70	6,40	3,33	1,66	4,16	0,22 x 0,44	3,0
100	100	DCE100UH	0,83/0,42	3,09	6,30	3,60	2,05	3,50	0,22 x 0,44	4,2
150	150	DCE150UH	1,25/0,63	3,09	6,90	3,60	2,05	4,10	0,22 x 0,44	5,3
250	160	DCE250UH	2,08/1,04	3,90	6,60	4,30	2,52	3,90	0,22 x 0,44	7,6
350	250	DCE350UH	2,92/1,46	3,90	7,00	4,30	2,52	4,30	0,22 x 0,44	8,7
500	300	DCE500UH	4,17/2,08	4,60	7,20	4,60	3,30	4,50	0,31 x 0,81	13,3
750	500	DCE750UH	6,25/3,13	5,60	7,60	5,10	4,00	4,90	0,31 x 0,81	20,3
1000	650	DCE1000UH	8,33/4,17	5,60	8,00	5,10	4,00	5,30	0,31 x 0,81	22,9
1500	1000	DCE1500UH	12,5/6,25	5,60	9,40	5,10	4,00	6,70	0,31 x 0,81	30,3
2000	1300	DCE2000UH	16,7/8,33	6,60	9,10	6,00	5,10	5,70	0,31 x 0,81	37,1
3000	2000	DCE3000UH	25,0/12,5	7,80	11,30	6,70	6,30	6,90	0,31 x 0,81	64,0
5000	3000	DCE5000UH	41,7/20,8	9,30	14,9	8,00	7,10	7,30	0,31 x 0,81	99,7

Primary and Secondary voltage links/jumpers supplied standard with all transformers.

Special voltages and VA sizes available upon request.

1 Note: For 750 through 2000 VA units actual overall depth is 0.24" plus the value in column B.

* See back cover for dimensional drawings.

All dimensions in inches

Series-B

Primary Voltage Secondary Voltage			600 12 x 24	575 11.5 x 23	550 11 x 22	  		60 Hertz		
VA Rating	CE VA Rating	Catalog Number	Output Amps	Overall Dimensions			Mounting Centers		Mounting Slot	Approx. Ship Weight Lbs.
				A	B	C	D	E	G X H	
50	50	DCE50QC	4,17/2,08	2,70	5,80	3,33	1,66	3,58	0,22 x 0,44	2,3
100	100	DCE100QC	8,33/4,17	3,09	6,30	3,60	2,05	3,50	0,22 x 0,44	4,2
150	150	DCE150QC	12,5/6,25	3,09	6,70	3,60	2,05	3,90	0,22 x 0,44	4,8
250	160	DCE250QC	20,8/10,4	3,90	6,20	2,52	2,52	3,50	0,22 x 0,44	6,4
350	250	DCE350QC	29,2/14,6	3,90	6,80	2,52	2,52	4,10	0,22 x 0,44	8,3
500	300	DCE500QC	41,7/20,8	4,60	6,80	3,30	3,30	4,50	0,31 x 0,81	11,8

Primary and Secondary voltage links/jumpers supplied standard with all transformers.

Special voltages and VA sizes available upon request.

* See back cover for dimensional drawings.

All dimensions in inches

SYNONYMOUS WITH QUALITY



Series-C

Primary Voltage Secondary Voltage			240 x 480 120 x 240	230 x 460 115 x 230	220 x 440 110 x 220	  		50/60 Hertz		
VA Rating	CE VA Rating	Catalog Number	Output Amps	Overall Dimensions			Mounting Centers		Mounting Slot	Approx. Ship Weight Lbs.
				A	B	C	D	E	G X H	
50	50	DCE50PH	0,42/0,21	2,70	5,90	3,33	1,66	3,69	0,22 x 0,44	2,5
100	100	DCE100PH	0,83/0,42	3,09	6,30	3,60	2,05	3,50	0,22 x 0,44	3,9
150	150	DCE150PH	1,25/0,63	3,09	6,90	3,60	2,05	4,10	0,22 x 0,44	5,2
250	160	DCE250PH	2,08/1,04	3,90	6,60	4,30	2,52	3,90	0,22 x 0,44	7,7
350	250	DCE350PH	2,92/1,46	3,90	7,20	4,30	2,52	4,90	0,22 x 0,44	9,4
500	300	DCE500PH	4,17/2,08	4,60	7,20	4,60	3,30	4,50	0,31 x 0,81	13,2
750	500	DCE750PH	6,25/3,13	5,60	7,20	5,10	4,00	4,50	0,31 x 0,81	18,0
1000	650	DCE1000PH	8,33/4,17	5,60	8,00	5,10	4,00	5,30	0,31 x 0,81	22,8
1500	1000	DCE1500PH	12,5/6,25	6,00	8,50	6,00	5,10	5,10	0,31 x 0,81	31,1
2000	1300	DCE2000PH	16,7/8,33	6,60	9,10	6,00	5,10	5,70	0,31 x 0,81	38,1
3000	2000	DCE3000PH	25,0/12,5	7,80	11,70	6,70	6,30	7,30	0,44 x 1,00	68,5
5000	3000	DCE5000PH	41,7/20,8	9,30	15,10	8,00	7,40	7,30	0,44 x 1,00	104,2

Primary and Secondary voltage links/jumpers supplied standard with all transformers.

Special voltages and VA sizes available upon request.

¹ Note: For 750 through 2000 VA units actual overall depth is 0.24" plus the value in column B.

* See back cover for dimensional drawings.

All dimensions in inches

Series-D

Primary Voltage Secondary Voltage			240 x 480 12 x 24	230 x 460 11.5 x 23	220 x 440 11 x 22	  		50/60 Hertz		
VA Rating	CE VA Rating	Catalog Number	Output Amps	Overall Dimensions			Mounting Centers		Mounting Slot	Approx. Ship Weight Lbs.
				A	B	C	D	E	G X H	
50	50	DCE50PC	4,17/2,08	2,70	5,90	3,33	1,66	3,69	0,22 x 0,44	2,5
100	100	DCE100PC	8,33/4,17	3,09	6,10	3,60	2,05	3,35	0,22 x 0,44	3,90
150	150	DCE150PC	12,5/6,25	3,09	6,90	3,60	2,05	4,10	0,22 x 0,44	5,2
250	160	DCE250PC	20,8/10,4	3,90	6,60	4,30	2,52	3,90	0,22 x 0,44	7,7
350	250	DCE350PC	29,2/14,6	3,90	7,20	4,30	2,52	4,90	0,22 x 0,44	9,5
500	300	DCE500PC	41,7/20,8	4,60	7,20	4,60	3,30	4,50	0,31 x 0,81	13,4

Primary and Secondary voltage links/jumpers supplied standard with all transformers.

Special voltages and VA sizes available upon request.

* See back cover for dimensional drawings.

All dimensions in inches



Series-E

Primary Voltage
Secondary Voltage

380/347
120 x 240



50/60 Hertz

VA Rating	CE VA Rating	Catalog Number	Output Amps	Overall Dimensions			Mounting Centers		Mounting Slot	Approx. Ship Weight Lbs.
				A	B	C	D	E		
50	50	DCE50LH	0,42/0,21	2,70	5,90	3,33	1,66	3,69	0,22 x 0,44	2,5
100	100	DCE100LH	0,83/0,42	3,09	6,30	3,60	2,05	3,50	0,22 x 0,44	4,3
150	150	DCE150LH	1,25/0,63	3,09	6,90	3,60	2,05	4,10	0,22 x 0,44	5,3
250	160	DCE250LH	2,08/1,04	3,90	6,60	4,30	2,52	3,90	0,22 x 0,44	7,9
350	250	DCE350LH	2,92/1,46	3,90	7,20	4,30	2,52	4,90	0,22 x 0,44	9,6
500	300	DCE500LH	4,17/2,08	4,60	7,20	4,60	3,30	4,50	0,31 x 0,81	13,6
750	500	DCE750LH	6,25/3,13	5,60	7,20	5,10	4,00	4,50	0,31 x 0,81	19
1000	650	DCE1000LH	8,33/4,17	5,60	8,00	5,10	4,00	5,30	0,31 x 0,81	23,5
1500	1000	DCE1500LH	12,5/6,25	6,60	8,50	6,00	5,10	5,10	0,31 x 0,81	31,6

Primary and Secondary voltage links/jumpers supplied standard with all transformers.

Special voltages and VA sizes available upon request.

1 Note: For 750 through 1500 VA units actual overall depth is 0.24" plus the value in column B.

* See back cover for dimensional drawings.

All dimensions in inches

Series-F

Primary Voltage
Secondary Voltage

380/347
12 x 24



50/60 Hertz

VA Rating	CE VA Rating	Catalog Number	Output Amps	Overall Dimensions			Mounting Centers		Mounting Slot	Approx. Ship Weight Lbs.
				A	B	C	D	E		
50	50	DCE50LC	4,17/2,08	2,70	5,90	3,33	1,66	3,69	0,22 x 0,44	2,5
100	100	DCE100LC	8,33/4,17	3,09	6,30	3,60	2,05	3,50	0,22 x 0,44	4,2
150	150	DCE150LC	12,5/6,25	3,09	6,90	3,60	2,05	4,10	0,22 x 0,44	5,3
250	160	DCE250LC	20,8/10,4	3,90	6,60	4,30	2,52	3,90	0,22 x 0,44	7,6
350	250	DCE350LC	29,2/14,6	3,90	7,20	4,30	2,52	4,90	0,22 x 0,44	9,3
500	300	DCE500LC	41,7/20,8	4,60	7,20	4,60	3,30	4,50	0,31 x 0,81	13,2

Primary and Secondary voltage links/jumpers supplied standard with all transformers.

Special voltages and VA sizes available upon request.

* See back cover for dimensional drawings.

All dimensions in inches

Series-G

Primary Voltage
Secondary Voltage

277
120



50/60 Hertz

VA Rating	CE VA Rating	Catalog Number	Output Amps	Overall Dimensions			Mounting Centers		Mounting Slot	Approx. Ship Weight Lbs.
				A	B	C	D	E		
50	50	DCE50IE	0,42	2,70	5,90	3,33	1,66	3,69	0,22 x 0,44	2,4
100	100	DCE100IE	0,83	3,09	6,10	3,60	2,05	3,35	0,22 x 0,44	4,1
150	150	DCE150IE	1,25	3,09	6,90	3,60	2,05	4,10	0,22 x 0,44	5,2
250	160	DCE250IE	2,08	3,90	6,60	4,30	2,52	3,90	0,22 x 0,44	7,6
350	250	DCE350IE	2,92	3,90	7,20	4,30	2,52	4,90	0,22 x 0,44	9,3
500	300	DCE500IE	4,17	4,60	7,20	4,60	3,30	4,50	0,31 x 0,81	13,3
750	500	DCE750IE	6,25	5,60	7,60	5,10	4,00	4,90	0,31 x 0,81	20,1
1000	650	DCE1000IE	8,33	5,60	8,00	5,10	4,00	5,30	0,31 x 0,81	22,6
1500	1000	DCE1500IE	12,50	5,60	9,40	5,10	4,00	6,70	0,31 x 0,81	31,1

Primary and Secondary voltage links/jumpers supplied standard with all transformers.

Special voltages and VA sizes available upon request.

1 Note: For 750 through 1500 VA units actual overall depth is 0.24" plus the value in column B.

* See back cover for dimensional drawings.

All dimensions in inches

SYNONYMOUS WITH QUALITY

