

| Date: | Project Name: | |
|-------|---------------|--|
| Туре: | Part Number: | |









HELIOS SERIES

WIDE WRAP AROUND MS



DESCRIPTION

The Helios series embraces a minimalist design while providing a wide array of features making this fixture adaptable to any indoor application. Utilize the colour and wattage selections built into the fixture to create the perfect look. Easy to install and built to last, this series is sure to impress.

FEATURES

- **DLC** Approved
- Built-in Microwave Sensor
- Dual Voltage 120-347V
- 0-10V Continuous Dimming
- Surface or Suspension Mounting options
- Easy and Safe Installation
- Frosted Polycarbonate Lens
- Rated Lifetime L70(hrs): >70,000
- Operation Temperature: -22°F to 122°F (-30°C to 50°C)
- Suitable for Damp Locations
- Includes Coverplate and V-Hangers
- CRI >80
- 7 year warranty

APPLICATIONS



Corridors



Education Facilities



Low Bay Application



Multi-res/Retirement















*THE MAXIMUM HEIGHT THIS FIXTURE CAN BE MOUNTED FOR OPTIMAL SENSOR FUNCTION IS 12-13FT. IF MOUNT-ED ABOVE THIS HEIGHT MOTION WILL NOT BE DETECTED **AS PRECISELY***









| Date: | Project Name: |
|-------|---------------|
| Туре: | Part Number: |

SPECIFICATION

| ORDER# | MODEL# | WATTS | VOLTAGE (V) | CCT (K) | SIZE | LUMENS | EFFICACY | CRI | | | | | | |
|--------|---------------------------------|-------|----------------|------------|----------|----------|----------|------------|----------|-----------|-----|---------|----------|-----|
| | | 30W | | | | | 3936 lm | 131.2 lm/W | | | | | | |
| | | 40W | | 3500K | | 5280 lm | 132 lm/W | >80 | | | | | | |
| | R38022 RENO-WHWR4-DV-MV-MCCT-MS | 50W | | | | 6650 lm | 133 lm/W | | | | | | | |
| | | 60W | | | | 8040 lm | 134 lm/W | | | | | | | |
| | | 30W | 120-347V | | 40001/ | 4200 lm | 140 lm/W | | | | | | | |
| D20022 | | 40W | | 400016 | | 5640 lm | 141 lm/W | | | | | | | |
| K38UZZ | | 50W | | | 120-347V | 120-347V | 120-347V | 120-347V | 120-3477 | 47V 4000K | 4FT | 7100 lm | 142 lm/W | >00 |
| | | 60W | | | | | 8580 lm | 143 lm/W | | | | | | |
| | | 30W | | | 500014 | | 5280 lm | 132 lm/W | | | | | | |
| | | 40W | | | | | | | 500016 | F000K | | 6650 lm | 133 lm/W | |
| | | 50W | | | 5000K | | 8040 lm | 134 lm/W | | | | | | |
| | | 60W | | | | 8100 lm | 135 lm/W | | | | | | | |

DLC INFORMATION

| ODDED# | ORDER# MODEL# | APPLICATION | DLC | | |
|------------------------------|----------------------------------|---|----------|----------|--|
| ORDER# | | AFFLICATION | STANDARD | PREMIUM | |
| R38022 RENO-WHWR4-DV-MV-MCCT | | Low-Bay Luminaires for Commercial and Industrial Buildings | - | S-NWTSGP | |
| | Direct Linear Ambient Luminaires | S-MTRPBQ | - | | |
| | | Stairwell and Passageway Luminaires | - | S-17P43M | |

ACCESSORIES

| ORDER# | MODEL# | DESCRIPTION |
|--------|-------------|---------------------|
| R83004 | RENO-EM-C08 | Emergeny LED Driver |



RENO-EM-C08







| Date: | Project Name: |
|-------|---------------|
| Туре: | Part Number: |

REMOTE OPTIONS

| ORDER# | MODEL# | DESCRIPTION |
|--------|-------------------|--------------------|
| R73002 | RENO-REMOTE-H | Remote Control |
| R73005 | RENO-REMOTE-H-ECO | ECO Remote Control |





RENO-REMOTE-H

RENO-REMOTE-H-ECO

DIMENSIONS

4FT.



