



SIMATIC S7-1200, Analog input, SB 1231RTD, 1 AI RTD, Pt100 and Pt1000

General information	
Product type designation	SB 1231, AI 1x16 bit RTD
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	5 mA
from backplane bus 5 V DC, typ.	20 mA
Power loss	
Power loss, typ.	0.5 W
Analog inputs	
Number of analog inputs	1; Resistance thermometer
permissible input voltage for current input (destruction limit), max.	±35 V
Technical unit for temperature measurement adjustable	Degrees Celsius/degrees Fahrenheit
Input ranges	
<ul style="list-style-type: none"> <li>• Voltage</li> <li>• Current</li> <li>• Thermocouple</li> <li>• Resistance thermometer</li> <li>• Resistance</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>No</li> <li>No</li> <li>Yes; Platinum (Pt)</li> <li>Yes; 150 Ω, 300 Ω, 600 Ω</li> </ul>
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>• -80 mV to +80 mV</li> <li>— Input resistance (-80 mV to +80 mV)</li> </ul>	<ul style="list-style-type: none"> <li>&gt;= 10 MOhm</li> </ul>
Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> <li>• Pt 100</li> <li>— Input resistance (Pt 100)</li> <li>• Pt 1000</li> <li>— Input resistance (Pt 1000)</li> <li>• Pt 200</li> <li>— Input resistance (Pt 200)</li> <li>• Pt 500</li> <li>— Input resistance (Pt 500)</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>100 Ω</li> <li>Yes</li> <li>1 000 Ω</li> <li>Yes</li> <li>200 Ω</li> <li>Yes</li> <li>500 Ω</li> </ul>
Input ranges (rated values), resistors	
<ul style="list-style-type: none"> <li>• 0 to 150 ohms</li> <li>• 0 to 300 ohms</li> <li>• 0 to 600 ohms</li> </ul>	<ul style="list-style-type: none"> <li>Yes</li> <li>Yes</li> <li>Yes</li> </ul>
Thermocouple (TC)	
Temperature compensation	
— parameterizable	No
Analog outputs	

Number of analog outputs	0
Cable length	
<ul style="list-style-type: none"> <li>shielded, max.</li> </ul>	100 m; shielded, twisted pair
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>Resolution with overrange (bit including sign), max.</li> <li>Integration time, parameterizable</li> <li>Interference voltage suppression for interference frequency <math>f_1</math> in Hz</li> </ul>	15 bit; + sign No 85 dB at 10 / 50 / 60 / 400 Hz
<b>Errors/accuracies</b>	
Temperature error (relative to input range), (+/-)	25 °C $\pm$ 0.1%, to 55 °C $\pm$ 0.2% total measurement range
Repeat accuracy in steady state at 25 °C (relative to output range), (+/-)	0.05 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1 =$ interference frequency	
<ul style="list-style-type: none"> <li>Common mode interference, min.</li> </ul>	120 dB
<b>Interrupts/diagnostics/status information</b>	
Alarms	Yes
Diagnostics function	Yes; Can be read out
Alarms	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes
Diagnoses	
<ul style="list-style-type: none"> <li>Wire-break</li> </ul>	Yes
Diagnostics indication LED	
<ul style="list-style-type: none"> <li>for status of the inputs</li> <li>for maintenance</li> </ul>	Yes Yes
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
<b>Ambient conditions</b>	
Free fall	
<ul style="list-style-type: none"> <li>Fall height, max.</li> </ul>	0.3 m; five times, in product package
Ambient temperature during operation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> <li>horizontal installation, min.</li> <li>horizontal installation, max.</li> <li>vertical installation, min.</li> <li>vertical installation, max.</li> </ul>	-20 °C 60 °C -20 °C 60 °C -20 °C 50 °C
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> <li>min.</li> <li>max.</li> </ul>	-40 °C 70 °C
Air pressure acc. to IEC 60068-2-13	
<ul style="list-style-type: none"> <li>Operation, min.</li> <li>Operation, max.</li> <li>Storage/transport, min.</li> <li>Storage/transport, max.</li> </ul>	795 hPa 1 080 hPa 660 hPa 1 080 hPa
Relative humidity	
<ul style="list-style-type: none"> <li>Operation at 25 °C without condensation, max.</li> </ul>	95 %
Pollutant concentrations	
<ul style="list-style-type: none"> <li>SO<sub>2</sub> at RH &lt; 60% without condensation</li> </ul>	SO <sub>2</sub> : < 0.5 ppm; H <sub>2</sub> S: < 0.1 ppm; RH < 60% condensation-free
<b>connection method</b>	
required front connector	Yes
<b>Mechanics/material</b>	
Enclosure material (front)	

• Plastic

Yes

#### Dimensions

Width	38 mm
Height	62 mm
Depth	21 mm

#### Weights

Weight, approx.	35 g
-----------------	------

**last modified:**

4/25/2024 