



SIMATIC S7-1200, Battery Board BB 1297 for long-term buffering of the real time clock, plug-in in the signal board receptacle of the S7-12XX (FW3.0 or higher); Battery (CR1025) not included in scope of delivery

General information	
Product type designation	BB 1297
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes
Diagnostics indication LED	<ul style="list-style-type: none"> for maintenance
	Yes; The maintenance LED (MAINT) of the PLC signals that the battery needs to be replaced.
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
Marine approval	Yes
Ambient conditions	
Free fall	<ul style="list-style-type: none"> Fall height, max.
	0.3 m; five times, in product package
Ambient temperature during operation	<ul style="list-style-type: none"> min. max.
	<ul style="list-style-type: none"> -20 °C 60 °C
Ambient temperature during storage/transportation	<ul style="list-style-type: none"> min. max.
	<ul style="list-style-type: none"> -40 °C 70 °C
Air pressure acc. to IEC 60068-2-13	<ul style="list-style-type: none"> Operation, min. Operation, max. Storage/transport, min. Storage/transport, max.
	<ul style="list-style-type: none"> 795 hPa 1 080 hPa 660 hPa 1 080 hPa
Relative humidity	<ul style="list-style-type: none"> Operation at 25 °C without condensation, max.
	95 %
Mechanics/material	
Enclosure material (front)	<ul style="list-style-type: none"> Plastic
	Yes
Dimensions	
Width	38 mm
Height	62 mm
Depth	21 mm
Weights	

Weight, approx.

40 g

last modified:

3/12/2024 