



# 7210-B

20 Amp, 250-Volt, 2-Pole, 2-Wire, Single Receptacle

20 Amp, 250-Volt, NEMA L2-20, 2-Pole, 2-Wire, Single Receptacle - BLACK

Leviton offers industrial, commercial and residential plugs and connectors for unlimited application settings. Plugs and connectors are provided in a range of ratings from 15 Amps to 60 Amps; the product line includes straight-blade and locking devices in all NEMA configurations, as well as locking devices in non-NEMA configurations. Versions include Hospital Grade, isolated ground, WetGuard, Dustguard, Python, power plugs, corrosion resistant plugs and connectors, power-interrupting devices, midget devices, and much more.

UPC Code : 078477835746

Country Of Origin : Mexico

NEMA :  L2-20R

## Technical Information

### Electrical Specifications

**Amperage** : 20 A

**Current Interrupting** : Certified for current interrupting at full rated current

**Dielectric Voltage** : Withstands 2000V per UL498

**Grounding** : Non-Grounding

**Pole** : 2

**Temperature Rise** : Max 30C after 250 cycles OL at 200 percent rated current

**Voltage** : 250 VAC

**Wire** : 2

### Environmental Specifications

**Environment** : Dry

**Flammability** : UL94V-2

**Operating Temperature** : -40° C to 75°C

### Material Specifications

**Base Material** : RTP

**Clamp Nuts** : Brass

**Color** : Black

**Contact - Spring Value** : 0.041 inch thick Brass

**Cover Material** : Nylon

**Ground Contacts** : Brass

**Ground Shunt** : Brass

**Grounding Screw** : Bronze

**Mounting Screws** : Zinc-Plated Steel 8-32

**Terminal Screws** : Brass 10-32

### Mechanical Specifications

**Product ID** : Ratings are permanently marked on device

**Screw Terminal Torque** : 14 in-lbs

**Terminal Accom.** : 16-8 AWG

**Terminal ID** : X,Y,Z, White, Green

### Product Features

**Color :** Black

**NEMA :** L2-20R

#{wiring\_diagram}

#{dimensional\_drawing}

**SPECIFICATION SUBMITTAL**

<b>JOB NAME:</b> <input type="text"/>	<b>CATALOG NUMBERS:</b> <input type="text"/>	<input type="text"/>
<b>JOB NUMBER:</b> <input type="text"/>	<input type="text"/>	<input type="text"/>

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at: [www.leviton.com](http://www.leviton.com)**

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:

[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

**© 2024 Leviton Manufacturing Co., Inc.**