



**Color :**  Brown

**UPC Code :** 078477168370

**Country Of Origin :** Mexico

**Available Colors :**



Ivory



White

# 1288

30 Amp, 120/277 Volt, Toggle Double-Throw Ctr-OFF Maintained Contact Double-Pole AC Quiet Switch, Extra Heavy Duty Spec Grade, Grounding, Back & Side Wired, - Brown

**ROHS Compliant :** Yes

## Technical Information

### AC Horsepower Ratings

**HP Rating :** 2HP-120V 2HP-240V-277V

### Electrical Specifications

**Amperage :** 30 A

**Dielectric Voltage :**  
Withstands 1500V for 1 minute

**Endurance :** 50,000 cycles minimum

**Grounding :** Self-Grounding

**Overload UL20 Test :** 100 cycles of OL at 4.8 times rated current

**Temperature Rise :** Maximum 30 degrees C rise

**Voltage :** 120/277 VAC

### Environmental Specifications

**Flammability :** Rated V-2 per UL 94

**Operating Temperature :** -40° C to 65°C

### Material Specifications

**Base Material :** Thermoplastic

**Color :** Brown

**Contact Material :** Silver Alloy

**Cover Material :** Thermoplastic

**Ground Clips :** Brass

**Grounding Screw :** Brass 8-32

**Strap Material :** Steel

**Terminal Screws :** Brass 8-32

**Toggle :** Polycarbonate

### Mechanical Specifications

**Product ID :** Ratings are permanently marked on device

**Screw Terminal Torque :** 14-18 in-lbs

**Terminal Accom. :** 14-#10 AWG back wired; #14-#12 AWG side wired

**Terminal ID :** Brass-Hot Black-Hot White-Neutral Green-Gnd

**Termination :** Back or Side Wire

### Product Features

**Body Material :** Thermoplastic

**Color :** Brown

**Device Type :** Toggle Switch

**Feature :** Maintained Contact CTR OFF

**Function :** Double-Pole Double-Throw

**Grade :** Extra Heavy-Duty Industrial Specification Grade

**Grounding :** Self-Grounding

**HP Rating** : 2HP-120V 2HP-240V-277V

**Strap Material** : Steel

**Voltage** : 120/277 VAC

Standards and Certifications

**ANSI** : C-73

**CSA C22.2 No. 111** : File #152105

**NEMA** : WD-1 & WD-6

**NOM** : 057

**RoHS** : Compliant

**UL Fed Spec WS896E** : File #E7458

**UL Standard** : UL 20

**Warranty** : 10-Year Limited

**SPECIFICATION SUBMITTAL**

|                                   |                                                    |
|-----------------------------------|----------------------------------------------------|
| <b>JOB NAME:</b><br><div></div>   | <b>CATALOG NUMBERS:</b><br><div></div> <div></div> |
| <b>JOB NUMBER:</b><br><div></div> | <div></div> <div></div>                            |

**Leviton Manufacturing Co., Inc**

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.  
T. Monday-Friday): +1-800-824-3005

**Leviton Manufacturing of Canada, Ltd.**

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·  
FAX: +1-800-824-3005 · [www.leviton.com/canada](http://www.leviton.com/canada)

**Leviton S. de R.L. de C.V.**

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)  
5386- 1797 · [www.leviton.com.mx](http://www.leviton.com.mx)

**Visit our Website at:** [www.leviton.com](http://www.leviton.com)

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

**Leviton has a global presence.**

If you would like to know where your local Leviton office is located please go to:  
[www.leviton.com/international/contacts](http://www.leviton.com/international/contacts)

© 2024 Leviton Manufacturing Co., Inc.