



UPC Code : 078477827659

Country Of Origin : Mexico

51120-3

Type 2 3-Phase Surge Panel with 4-Mode Protection

120/208V 3-Phase WYE Panel Protector, 4-Mode Protection, 50kA Max Surge Current Rating, NEMA 1 Enclosure, UL 1449 4th Edition Type 2

DISCONTINUED

Suggested Replacement SKUs: :

Leviton's Surge Protection Devices can be used individually or as part of a coordinated application strategy, to protect sensitive electronic equipment, in industrial, commercial and residential locations, from the stress and degradation inflicted by voltage transients. Leviton Surge Protection Devices are compliant with UL 1449 Standards. Leviton's outstanding Surge Protection Devices divert damaging voltage transients, or surges, away from electronic equipment. Transients are diverted away from sensitive micro circuitry, providing protection against catastrophic failure, costly downtime and data disruptions.

Technical Information

Electrical Specifications

EMI/RFI Noise Rejection : (-6 to -28dB @ 100KHz to 100MHz)

Frequency : 50/60Hz

Recommended Circuit Breaker Rating : 20A, 120 /208V

Surge Technology : 40mm MOV Design

Voltage Configuration : 120 /208 V, 3-Phase WYE

Material Specifications

Outer Enclosure : Powder Coated Steel

Performance Data

MCOV L-L : 300

MCOV L-N : 150

Maximum Surge Current, Per Mode (Per Phase) : 50kA (50kA)

Nominal Discharge Current Rating : 3kA

Environmental Specifications

Enclosure : Type 1

Flammability : Rated V-2 per UL 94

Operating Temperature : -10° C to 60°C

Relative Humidity : 5% to 95% non-condensing

Storage Temperature Range : -20C to 85C

Mechanical Specifications

Connection Type : Parallel - Hardwired via 12 AWG Wire

Diagnostics : Protection Status LEDs

Surge Counter : No

Product Features

Replaceable Modules : No

Short Circuit Current Rating :
10kA

VPR L-L : 1200

VPR L-N : 800

Standards and Certifications

**ANSI/IEEE Category A, B and
C : C-62.41 & 62.45**

**UL 1449 4th Edition : cULus
Listed Type 2**

Warranty

**Connected Equipment
Coverage : Up to \$25,000**

Warranty : 5-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/>	
JOB NUMBER: <input type="text"/>	<input type="text"/>	<input type="text"/>

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.