



Color :  Brown

UPC Code : 078477226506

Country Of Origin : Mexico

NEMA :  5-15R

Available Colors :



Ivory



Light Almond



White

5225

15 Amp, 120 Volt, Duplex Style Single-Pole / 5-15R AC Combination Switch, Commercial Grade, Grounding, Side Wired, Brown

15 Amp, 120 Volt, Duplex Style Single-Pole / 5-15R AC Combination Switch, Commercial Grade, Grounding, Side Wired, - Brown

- Functional – provides multiple controls in a single-gang space
- Durable – impact-resistant thermoplastic nylon construction
- Compatible – designed for use with Leviton traditional wallplates

Technical Information

AC Horsepower Ratings

HP Rating : 1/2HP-120V

Max. Amperage : 12 Amp

Electrical Specifications

Dielectric Voltage :

Withstands 1500V for 1 minute

Grounding : Grounding

Overload UL20 Test : 100

cycles of OL at 4.8 times rated current

Pole : 1

Receptacle Amperage : 15 Amp

Receptacle Voltage : 125V AC

Switch Amperage : 15 Amp

Switch Voltage : 120V AC

Temperature Rise : Maximum 30 degrees C rise

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 65°C

Material Specifications

Actuator Material : Thermoplastic

Body Material : Thermoplastic

Color : Brown

Strap Material : Steel

Mechanical Specifications

Product ID : Stamped on Strap

Terminal Accom. : 14-12 AWG

Terminal ID : Brass-Hot Black-Hot White-Neutral Green-Gnd

Termination : Side

Torque Range : 14 – 18 in.-lbs

Product Features

Amperage : 15 A

Color : Brown

Feature : Single-Pole / 5-15R

NEMA : 5-15R

Product Type : Switch/Outlet Combo

Type : Duplex Style
Combination Switch

Voltage : 120 VAC

Warranty : 2-Year Limited

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 111 : File
#152105

NEMA : WD-1 & WD-6

NOM : 057

UL Standard : UL 20

Warranty : 2-Year Limited

Features and Benefits

- AC quiet switches have silver-cadmium oxide contacts and receptacles have double-wipe contacts for maximum conductivity
- All devices have grounding screw
- Side wired with terminal screws that accept up to #12 copper or copper-clad wire
- Fit standard wallboxes
- Break-off tabs on devices with AC quiet switches permit conversion to seperate feeds
- Backed by a Limited Two-Year Warranty

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS:
JOB NUMBER: 	

Leviton Manufacturing Co., Inc
201 North Service Road, Melville, NY 11747
Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.
165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.
Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com
© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.
If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

