



1221-7PR

20 Amp, 277 Volt, Toggle Pilot Light - Illuminated ON - Req. Neutral Single-Pole AC Quiet Switch, Industrial Grade, Self Grounding, Back & Side Wired, - Red

Leviton's Industrial Grade AC toggle switches for extra heavy-duty applications represent top-of-the-line quality and peak performance. Leviton uses the finest materials available and the highest production standards to produce industrial switches of unmatched versatility and reliability.


Technical Information

Color :  Red

UPC Code : 078477240625

Country Of Origin : Please Contact Customer Service

Available Colors :



AC Horsepower Ratings

HP Rating : 2HP-277V

Max. Amperage : 16 Amp

Electrical Specifications

Amperage : 20 A

Dielectric Voltage :
Withstands 1500V for 1 minute

Endurance : 50,000 cycles minimum

Grounding : Self-Grounding

Overload UL20 Test : 100 cycles of OL at 4.8 times rated current

Temperature Rise : Maximum 30 degrees C rise

Voltage : 277 VAC

Environmental Specifications

Flammability : Rated V-2 per UL 94

Operating Temperature : -40° C to 65°C

Material Specifications

Base Material : Thermoplastic

Color : Red

Contact Material : Silver Alloy

Cover Material : Thermoplastic

Ground Clips : Brass

Grounding Screw : Brass 8-32

Strap Material : Steel

Terminal Screws : Brass 8-32

Toggle : Polycarbonate

Mechanical Specifications

Product ID : Ratings are permanently marked on device

Screw Terminal Torque : 14-18 in-lbs

Terminal Accom. : 14-#10 AWG back wired; #14-#12 AWG side wired

Product Features

Actuator Material : Polycarbonate

Body Material : Thermoplastic

Color : Red

Device Type : Toggle Switch

Feature : Pilot Light - Illuminated ON - Req.

Terminal ID : Brass-Hot Black-
Hot White-Neutral Green-Gnd

Neutral|Illuminated - Load ON
(Pilot Light)

Termination : Back or Side
Wire

Function : Single-Pole

Grade : Extra Heavy-Duty
Industrial Specification Grade

Grounding : Self-Grounding

HP Rating : 2HP-277V

Strap Material : Steel

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 111 : File
#152105

NEMA : WD-1 & WD-6

NOM : 057

RoHS : Compliant

UL Fed Spec WS896E : File
#E7458

UL Standard : UL 20

Warranty : 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME: 	CATALOG NUMBERS:
JOB NUMBER: 	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.

T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·

FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)

5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:

www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.