

5371



UPC Code : 078477823484

Country Of Origin : Mexico

NEMA :  5-30R

30 Amp, 125 Volt, 2P, 3W, Flush Mtg Receptacle, Straight Blade, Industrial Grade, Grounding, Black

30 Amp, 125 Volt, NEMA 5-30R, 2P, 3W, Flush Mtg Receptacle, Straight Blade, Industrial Grade, Grounding, , Side Wired, Steel Strap, - Black

ROHS Compliant : Yes

Leviton's line of Extra Heavy-Duty Industrial Grade receptacles are designed and manufactured to withstand the harsh conditions typically associated with industrial environments. Available in a wide variety of configurations, including isolated ground, tamper-resistant, hospital grade, etc., these Industrial Grade devices are the electrical contractor's choice for use in factories, schools, hospitals and commercial office buildings.

Technical Information

<u>AC Horsepower Ratings</u>	<u>Electrical Specifications</u>
At Rated Voltage : 2 HP	Amperage : 30 A
	Current Limiting : Full Rated Current
	Dielectric Voltage : Withstands 2000V per UL498
	Grounding : Grounding
	Pole : 2
	Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current
	Voltage : 125 VAC
	Wire : 3
<u>Environmental Specifications</u>	<u>Material Specifications</u>
Flammability : Rated V-2 per UL 94	Body Material : Nylon
Operating Temperature : -40° C to 60°C	Color : Black
	Face Material : Nylon
	Line Contacts : Brass Double-Wipe
	Strap Material : Galvanized Steel
<u>Mechanical Specifications</u>	<u>Product Features</u>
Product ID : Ratings are permanently marked on device	Color : Black
Terminal Accom. : Up to 4 AWG	Device Type : Power Device
	NEMA : 5-30R

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Standards and Certifications

ANSI : C-73

CSA C22.2 No. 42 : File
152105


NEMA : WD-6

NOM : 057

UL498 : File E13399

Warranty : 10-Year Limited

Wiring Diagram



SPECIFICATION SUBMITTAL

JOB NAME: <input type="text"/>	CATALOG NUMBERS: <input type="text"/> <input type="text"/> <input type="text"/> <input type="text"/>	
JOB NUMBER: <input type="text"/>		

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.
T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)
5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without
notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.