HUBBELL
Premise Wiring

Category 6 XCELERATOR™ Jack

By Hubbell Premise Wiring
Catalog # HXJ6EI

Telephone/Data, Jack, XCELERATOR, Cat 6.

Features

- Third Party Verified Category 6 Component Compliant
- Exclusive 1-Punch Termination Reduces Termination Time by 75%
- Mating Cycles Exceed Industry Standard by Four Times
- Bulk Packaging Reduces Excess Waste on the Job

Performance

TIA Cat 6 Component, Third Party Verified

General

Catalog Number	HXJ6EI
Construction Material - Main	Thermoplastic
Contact	IDC: Phosphor Bronze with 100 Micro-Inch Tin Over Plating
Contact Point Material	Beryllium Copper with Gold Over Plating
EU RoHS Indicator	Yes
Item Type	Modular Jack
Material - Housing	High-impact thermoplastic (UL 94V-0)
Material - Mounting Hardware	Keystone
Operating Cycles	2000 Plug
Series	Cat 6 UTP
Size	0.86 (22) x 0.67 (17) x 1.29 (33)
Specifications	- Housing - High impact thermoplastic (UL 94 V-0) - IDC Contact - Phosphor bronze with 100 micro-inch tin over nickel under plating - Nose Contact - Beryllium copper with precious metal plating with nickel under-plating

Style	RJ-45 Jack
Temperature Rating	Max Continu- 75° C, Minimum- -40° C Sans impact
UPC	662620825267

Dimensions

Display Size	Standard Sized Product

Electrical Ratings

Connectivity	RJ45 Jack to IDC Punch Down
Contact Resistance	100 Ohm
Withstand Voltage	1,000 Vac @ 60 Hz

Certifications And Compliance

Industry Standard(s)	- ANSI/TIA/EIA-568 Category 6 component - UL 1863 - Communications-Circuit Accessory - IEC60512-99-002 POE Disconnection Endruance - UL 2043 - Suitable for Air-Handling Spaces - RoHS Compliant

Logistics

Carton Quantity	25
Number of Pieces in Package	1

Product Assets

Catalog Page - PREM A6 CatalogPage
Catalog Page - PREM B5 CatalogPage
Catalogs - Premise Wiring Catalog
Literature - HDPJ High Density Jack Panels
Specifications - HXJ6EI Specification Sheet French

A Hubbell brand