

Eaton PSS55D

Catalog Number: PSS55D

Power Supply Switcher, IP20 enclosure, 20-14 AWG wire size, 2.3A rated operational current, 55W, Three-phase, 480-600V input voltage, 24 Vdc output voltage, 0.07A/phase input current, 15A inrush current, 47-63 Hz, TS35 rail or chassis mount



General specifications

Product Name	Catalog Number
Eaton PSG general purpose power supply	PSS55D
	UPC
	782116199549
Product Length/Depth	Product Height
7.5 in	4 in
Product Width	Product Weight
9 in	3.05 lb
Warranty	Compliances
Eaton Selling Policy 25-000, one (1) year CE Marked from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	Certifications
	UL 508
	F47 Certified
	CSA Certified

Product specifications

Special features

Convection cooling, finger-safe cover, short-circuit protection, auto restart

Operating temperature - max

50 °C

Operating temperature - min

-25 °C

Power consumption

55 W

Phase

Three-phase

Frequency rating

47-63 Hz

Mounting Method

TS35 rail or chassis

Output voltage

24 V

Enclosure

IP20

Input voltage

480-600 V

Series

PSS

Rated operational current

2.3 A

0.07 A input

15 A inrush

10 A surge

Resources

Multimedia

[How to size and select a Power Supply](#)

Specifications and datasheets

[Eaton Specification Sheet - PSS55D](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia