

## Data sheet

## 6GK7342-5DA03-0XE0

### product type designation



### CP 342-5

Communications processor CP 342-5 for connection of SIMATIC S7-300 to PROFIBUS DP, S5-compatible, PG/OP and S7 communication.

### transfer rate

transfer rate	9.6 kbit/s ... 12 Mbit/s
• at the 1st interface / according to PROFIBUS	

### interfaces

number of interfaces / according to Industrial Ethernet	0
number of electrical connections	
• at the 1st interface / according to PROFIBUS	1
• for power supply	1
type of electrical connection	
• at the 1st interface / according to PROFIBUS	9-pin Sub-D socket (RS485)
• for power supply	4-pole terminal block

### supply voltage, current consumption, power loss

type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
• from backplane bus / at DC / at 5 V / typical	0.15 A
• from external supply voltage / at DC / at 24 V / typical	0.25 A
power loss [W]	6.75 W

### ambient conditions

ambient temperature	
• during operation	0 ... 60 °C
• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP20

### design, dimensions and weights

module format	Compact module S7-300 single width
width	40 mm
height	125 mm
depth	120 mm
net weight	0.3 kg

### product features, product functions, product components / general

number of units	
-----------------	--

**performance data / open communication**

number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum

16

data volume

- as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum

240 byte

**performance data / PROFIBUS DP**

service / as DP master

- DPV0

Yes

number of DP slaves

- on DP master / operable

124

data volume

- of the address range of the inputs / as DP master / total
- of the address range of the outputs / as DP master / total
- of the address range of the inputs / per DP slave
- of the address range of the outputs / per DP slave
- of the address range of the diagnostic data / per DP slave

2160 byte

2160 byte

244 byte

244 byte

240 byte

service / as DP slave

- DPV0

Yes

data volume

- of the address range of the inputs / as DP slave / total
- of the address range of the outputs / as DP slave / total

240 byte

240 byte

**performance data / S7 communication**

number of possible connections / for S7 communication

- maximum

16

**performance data / multi-protocol mode**

number of active connections / with multi-protocol mode

- without DP / maximum
- with DP / maximum

32

28

**performance data / telecontrol**

protocol / is supported

- TCP/IP

No

**product functions / management, configuration, engineering**

configuration software

- required

STEP 7 V5.1 SP2 or higher / STEP 7 Professional V12 (TIA Portal) or higher

**standards, specifications, approvals**

reference code

- according to IEC 81346-2:2019

KEC

**standards, specifications, approvals / Environmental Product Declaration**

Environmental Product Declaration

Yes

Global Warming Potential [CO2 eq]

- total
- during manufacturing
- during operation
- after end of life

229.03 kg

17.48 kg

211.2 kg

0.35 kg

**further information / internet links**

internet link

- to web page: selection aid TIA Selection Tool
- to website: Industrial communication
- to web page: SiePortal
- to website: Image database
- to website: CAx-Download-Manager
- to website: Industry Online Support

<https://www.siemens.com/tstcloud>  
<https://www.siemens.com/simatic-net>  
<https://sieportal.siemens.com/>  
<https://www.automation.siemens.com/bilddb>  
<https://www.siemens.com/cax>  
<https://support.industry.siemens.com>

**security information**

security information

Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks. In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected

to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit [www.siemens.com/cybersecurity-industry](http://www.siemens.com/cybersecurity-industry). Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under [https://www.siemens.com/cert. \(V4.7\)](https://www.siemens.com/cert. (V4.7))

## Approvals / Certificates

### General Product Approval



[Declaration of Conformity](#)



### For use in hazardous locations

### Marine / Shipping



FM

[CCC-Ex](#)



### Environment

[Confirmation](#)



last modified:

8/22/2024